

PRICE BID**DILIP KULKARNI & ASSOCIATES - ARCHITECTS, INTERIOR, LANDSCAPE DESIGNER & SURVEYOR.**

Add: 15/3, 2nd Floor, 'C' Wing, Metro House, Opp. Hotel Delhi Darbar, Shahid Bhagat Singh Road, Colaba, Mumbai 400 001.

Mobile - Mr. Rajan - 98200 76349 / 93216 29231 E-Mail - dkulkarniasso@gmail.com

NAME OF CLIENT: - **STATE BANK OF INDIA- POYNAD BRANCH**
ADDRESS: - **GROUND FLOOR, SHOP NO-1,2,3 ,SUPER COMPLEX, NEAR APLA BAZAR,
PEN ,ALIBAG ROAD. POYNAD-08**NATURE OF WORK: - **FURNITURE WORK**

NO.	Particulars	Qty.	Rate	Amount
	<u>FURNITURE</u>			
{A}	<u>COUNTERS</u>			
A01	<p>SINGLE WINDOW COUNTER</p> <p>Table Size - 5'-0" X 2'-6" X 3'-0" Side Table - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing and Fixing cash counter with side table in made of 19 mm thk. BWR (ISI 303) ply frame work for top, stiffner, verticals, shelves, apron, sides, drawer unit, shutters, customer Top, foot rest, 12mm thick BWR (ISI 303) ply for drawer sides, Sliding shutters, front Apron and 6mm thick BWR (ISI 303) ply for side table back, drawer bottom, drawer unit back along with matching color PVC laminate edge bidding & teak wood supports for fixing of top. Cash counter shall have 750mm in Depth and 900mm /1200mm in height or as per Bank's Requirement.</p> <p>The Cash counter writing top including customer top and side table top and 1.00mm thk. appd. color solid core laminate along with 12mm thick PLAIN Glass partition fixed above customer top upto 5'-5" in ht.</p> <p>The glass fixed with "D" type Stainless Steel bracket. The Cash counter shall have 1 No. of drawer unit having pencil drawer 4" deep & 3 Nos. of equal drawers below pencil drawer or as per the Bank requirements and side table shall have 2 Nos. of drawers at top and sliding shutters below the drawers.</p> <p>All the external surfaces i.e. counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick Solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/ make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles, Stainless Steel Grommet (wire manager), 2" dia S.S. Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S. Drawer chanel Powder Coated CPU Hanger etc. complete as per detail drawing and instructions of the Architect/Engineer.</p> <p style="text-align: right;">Mode Of Measurement - Length In Running Feet</p>	5.00	RFT	
<input checked="" type="checkbox"/>	RATE IN WORDS			
A02	<p>OFFICER WITH SIDE TABLE</p> <p>Table Size - 4'-6" X 2'-3" X 2'-6" Side Table - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing & Fixing Officer's Table With Side Table made out of 19mm thick BWR (ISI 303) ply frame work for table, side table, sides, top, front apron, shutters, unit sides, 12mm thk BWR (ISI 303)ply for drawer sides, key board sides, sliding shutters, foot</p>			

	<p>rest,6mm thick BWR (ISI 303) ply for back, drawer unit back, drawer bottom etc. with matching color PVC laminate edge bidding etc. complete.</p> <p>The table front shall have 12mm thick BWR (ISI 303) ply panels with 4" X 12mm thk. Border along with one drawer unit with one drawer for pencil tray, three Nos. of equal drawers, key board drawer, CPU Hanger & side table shall have 3" deep 2 Nos. drawer at top & openable shutter below the drawers etc. complete.</p> <p>All the external surfaces i.e.counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick full core Solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/ make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles,Stainless Steel Grommet (wire manager), 2" dia M.S.Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S.Drawer chanel Powder Coated CPU Hanger including supply & fixing flat screen holder - single arm (ebco make)etc. complete as per detail drawing and instructions of the Architect/Engineer.</p>				
Mode Of Measurement - Per Number		5.00	NOS.		
RATE IN WORDS					
A03	<p>OFFICER WITHOUT SIDE TABLE</p> <p>Table Size - 4'-6" X 2'-3" X 2'-6"</p> <p>Do as above Item No. A02 but table shall not have side table but shall have drawer pederstal and finish with 1 mm thk approved color laminate.etc. complete as per detail drawing & instructions of the Architect / Engineer.</p>				
Mode Of Measurement - Per Number		2.00	NOS.		
RATE IN WORDS					
A04	<p>BRANCH MANAGER TABLE WITH SIDE TABLE</p> <p>Table Size - 6'-0" X 2'-6" X 2'-6" Side Table - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing & Fixing Branch Manager Table with side table made out of 19mm thick BWR (ISI 303) ply frame work for table and side table tops, sides, apron, shelves, drawer units, shutters, drawers front, stiffeners, borders, 12mm thick BWR (ISI 303) ply for drawer sides, keyboard, borders, foot rest and 6mm thick BWR (ISI 303) ply for drawer unit back, drawer bottom, side unit back, grooves etc.</p> <p>with matching color PVC laminate edge beading. The table shall have one drawer unit with one tea tray, one pencil tray100 MM deep & 3 Nos. of equal drawers below.</p> <p>The side table shall have drawers at top & Openable shutters below along with provision for C.P.U. Hanger.</p> <p>The table shall have 750 mm in height and side table shall have 750 mm in height. table top & side table top shall finished with 1 mm thk. Appd. Laminate Finish on table top.</p> <p>All the external surfaces i.e.counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick approved solid core laminate finish and 0.8mm thick white laminate for</p>				

	internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles,Stainless Steel Grommet (wire manager), 2" dia M.S.Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S.Drawer chanel Powder Coated CPU Hanger including supply & fixing flat screen holder - single arm (ebco make)etc. complete as per detail drawing and instructions of the Architect/Engineer.				
	<u>Mode Of Measurement</u> - Per Number	1.00	NOS.		
RATE IN WORDS					
A05	CHEQUE WRITING DESK Providing & Fixing Cheque writing desk made out of 19mm Thk. BWR (ISI 303) ply Framework for verticle , Sides, Bottom, Back & 10mm Thk. Glass top in one piece with 8mm thk. Glass verticle at 4" c/c. or as per bank requirement. All external & internal surfaces shall have 1mm. Thk approved color laminate including edges etc. complete as per the detail drawing & instructions of Architect/ Engineer.				
	<u>Mode Of Measurement</u> - Length In Running Feet	4.00	RFT		
RATE IN WORDS					
A TOTAL OF TABLE					
{B}	<u>FULL HEIGHT PARTITION</u>				
B01	BOTH SIDE LAMINATE FINISH PARTITION INCLUDING DOOR Providing and Erecting in position approximate 9'-0" to 10'-0" in height partitions to be made out of 2" X 2" X 1.5mm thick Aluminum Tubular section frame work 2'-0" c/c bothways (Vertical & Horizontal) fixed with 2" X 2" X 2.5mm thick Aluminum Angle Cleats with Pan Headed Screws covered with 9 mm thk. BWR Ply (ISI 303 Grade) from both sides fixed with Flat Headed Metal Screws. The aluminum members of partition shall rigidly fixed to the existing Ceiling / Floors / Beams & Side Walls, whichever is applicable & as directed, the alternate members and corner members fixed upto existing Slab, Beams, whichever applicable. All exposed surfaces of the partition shall have approved make / color 1.0 mm thick solid core laminate from both sides or as per site requirements etc. complete. The necessary openings in the partitions shall be provided for A.C. Grill, Electrical Conduits, Electrical Switches, Light Fixtures, A.C. Opening, etc. complete as per detail drawing & instructions of Architect/ Bank's Engineer. <u>Note</u> :- Height of the partitions upto sofit of false ceiling shall be considered for payment.				
	<u>Mode Of Measurement</u> - Length X Height	400.00	SFT		
RATE IN WORDS					

B02	<p>BOTH SIDE LAMINATE PARTLY GLAZED 10MM THK. GLASS PARTITION INCLUDING DOOR</p> <p>Do as above ITEM NO.B01 (Both side laminate partition) but partition shall have both side approved make / colour 1.00mm thk.solid core laminate Appd. color laminate finish equivalent make 10 mm thick plain glass to be fixed with Brush finished Stainless Steel Runner for sides, top & bottom etc. complete as per the site requirements, detail drawing and instructions of Architect / Engineer.</p>				
<u>Mode Of Measurement</u> - Length X Height		110.00	SFT		
RATE IN WORDS					
B03	<p>12 MM THK. TOUGHENED GLASS PARTITION</p> <p>Do as above ITEM NO. B01. but partition shall have 12 mm thk. TOUGHENED glass for full height partition in single piece or 1 or 2 pieces (minimum 2400mm in length) with computerised diamond cut & diamond edge polish. The TOUGHEN Glass fixed with Brush finished Stainless Steel Runner for top, bottom, sides or as per site requirements including making required cutouts/ holes for Locks, Handles, "V" cut grooves to be filled with "T" Section in S.S.finish from both the ends etc. along with Sunk Headed Metal Screws, adhesive, nails etc. complete as per site requirements detail drawing & instructions of Architect / Engineer.</p>				
<u>Mode Of Measurement</u> - Length X Height		400.00	SFT		
RATE IN WORDS					
B04	<p>LOW HIGHT PARTITIONS</p> <p>BOTH SIDE LAMINATE PARTLY 10MM THK. GLASS</p> <p>Do as above ITEM NO.B01 (Both Side Laminate), but low height partition shall have 4'-6" in height . aluminium framework (Upto 3') shall be at 1'-6" C'C covered with 9 mm thk. BWR ply finish with 1 mm thk. solid core laminate appd color laminate. 10 mm thk. Plain glass to be fixed above 3'-0" in height or as per detail drawing. Glass to be fixed S.S. Finish approved bracket etc. complete as per the site requirements, detail drawing and instructions of Architect / Engineer.</p>				
<u>Mode Of Measurement</u> - Length X Height		60.00	SFT		
RATE IN WORDS					
B TOTAL OF PARTITIONS					
C	DOOR				
C01	<p>12MM THK. TOUGHENED GLASS DOOR WITH DOOR FRAME</p> <p>Providing and Fixing Main doors made of Sait Gobain / Asahi India make 12mm thk. edge toughened glass in single piece with computerised diamond cut and diamond polish for Main doors including making required cutouts, holes for locks, handles, pivot, patch fittings, corner fittings, hinges etc. The rate is inclusive of supply and fixing of Blumor equivalent make floor spring, Pivot (Top & Bottom) patch fitting with cover plate,</p>				

	Locks, Signages with necessary hardware etc. complete as per site requirement and instructions of the Architect/ Engineer. <u>Mode Of Measurement</u> - Length X Height	75.00	SFT		
RATE IN WORDS					
C02	COLLAPSIBLE DOOR Providing & Fixing steel collapsible gate with single or double leaf with necessary heavy duty Standard Steel Sections with Steel Rollers, Steel Guides Stopper, Pivots on both sides Locking Arrangements etc. including approved color Enamel paint etc. complete as per instruction of the Architect/Engineer. <u>Mode Of Measurement</u> - Length X Height	110.00	SFT		
RATE IN WORDS					
C03	FIRE DOOR FOR SERVER DOOR Providing & Fixing G.I. fire door single leaf as per below specifications: Frame: GI 1.60 mm Shuter: GI 1.20 mm shutter width / active shutter width :984 mm Frame Profile (D x H): 105 mm x 57 mm Frame Joint Type: Butt Type Frame Rebate: Single Under Cut: 9.00 mm Infill Material: Rockwool / HONEYCOMB Vision Panel Active (VPW x VPH) : 300 mm x 300 mm , 6mm Glass(Fire Shutter Thickness: 46 mm Finish : Powder coating Ball bearing: Butt Hinges Lock: Mortise Dead Lock with 70 mm cylinderrl, Handle: S.S. Finish Surface door closure with standard Arm <u>Mode Of Measurement</u> - Length X Height	25.00	SFT		
RATE IN WORDS					
C04	TRAP DOOR ROLLING SHUTTER Providing & Fixing trap door for Rolling Shutter made out of 50mm X 50mm II Class C.P.T.Wood frame work covered with 9 mm thick BWR ply from one side for shutters & 50 mm X 75 mm II class C.P.T.W. outer frame with vertical supports upto RCC slab. All the exposed surfaces shall be finish with approved make 1.0mm thick WHITE color laminate on outer side & 3 coats of enamel paint on internal side including necessary approved make/design S.S. Hinges, Concealed side including necessary approved make/design S.S. Hinges, Concealed Handle, S.S. Stopper, S.S.Locks etc. complete as per requirements of Air Conditioning Co. & instructions of the Architect / Engineer. <u>Mode Of Measurement</u> - Length X Height	100.00	SFT		
RATE IN WORDS					
C TOTAL OF DOORS					
{D}	PANELLING/WALL CLADDING				
D01	LAMINATE PANELLING Providing and Fixing laminate finish paneling for walls, columns etc. made out of 2"X 1" X 1.5 mm thick Aluminum Tubular frame				

	<p>work at every 1'-6" c/c (Vertical /Horizontal) both ways, covered with 12 mm thk. exterior grade particle board upto ceiling height etc. complete.</p> <p>All the exposed surfaces of the paneling shall be finish with approved make/color 1.00mm thk. solid core laminate upto ceiling height along with groove at junction of laminate etc. complete as per site requirements, detail drawing and the instructions of the Architect/Engineer.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	900.00	SFT		
RATE IN WORDS					
D02	<p>3 mm thk ACP PANELLING (INTERNAL GRADE)</p> <p>Providing and Fixing A.C.P. finish paneling for walls, columns etc. made of 50 mm X 25 mm X 1.5mm thick Aluminium Tubular frame work at every 450 mm c/c (Vertical/Horizontal) both ways upto ceiling height.</p> <p>All the exposed surfaces of the paneling shall be finish with approved make/color 3.0mm thick A.C.P. finished with upto ceiling height along with 6mm wide groove etc. complete as per site requirements, detail drawing and the instructions of the Architect/Engineer.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	260.00	SFT		
RATE IN WORDS					
D03	<p>ACP PANELLING (EXTERNAL GRADE)</p> <p>Designing, providing, custom fabricating & installing Aluminium cladding system of flexibond (Nano white - FB 314) or equivalent make exterior grade ACP panel (0.25 mm thk + 2.5 mm thk core + 0.25 mm thk) both side and aluminium framework as per the given elevation drawings and at all levels and floors / heights.</p> <p>The system is to be designed to with stand and shall be fixed to the RCC structure (structural support only) and / or to the M.S. sub structure(Structural supports only) with sheet metal screws, clamps, brackets and anchor fasteners as approved by the Architect/Engineer.</p> <p>All extruded aluminium sections including cleats shall be minimum 3mm thick. All aluminium extruded sections shall be of 6063 T5 or T6 alloy conforming to ASTM B221. Rate shall include handling, fabricating & fixing ACP panels. Rate shall include providing open cell polyethylene backer rod, weather sealant, shims etc. The weather sealant silicon shall be Dow Corning 789 (or as per approved by the Architect) for vertical application. Rate also includes scaffolding for cladding work.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	310.00	SFT		
RATE IN WORDS					
D04	<p>8 MM THK CALCIUM SILICATE PANELING</p> <p>Providing and Fixing laminate finish paneling for walls, columns etc. made out of 2"X 1" X 1.2mm thick Aluminum Tubular frame work at every 1'-6" c/c (Vertical /Horizontal) both ways, covered with 8 mm thk. calcium silicate board upto ceiling height with Sunk Headed Metal Screws as per the site requirements in required shape.</p>				

	All the exposed surfaces of the paneling shall be finish with approved make/color two hours fire rated paint in two coats etc. complete as per site requirements, detail drawing and the instructions of the Architect/Engineer.				
	<u>Mode Of Measurement</u> - Length X Height	195.00	SFT		
RATE IN WORDS					
D TOTAL OF PANELLING					
{E}	<u>FALSE CEILING</u>				
E01	<p>GYPNUM FALSE CEILING</p> <p>P/Fixing Gypsum Board false ceiling of Gypsum India or equivalent make. <u>METALLIC GRID</u> (conforming to IS:2095:1982): - The metallic grid shall consists of GI Perimeter channels of size 27mm X 0.5mm thick having one flange of 20mm & another flange of 30mm, GI Intermediate channel of size 45mm X 0.9mm thick with two flange of 15mm each at 1200mm center to center, GI hanger of size 25mm X 10mm X 0.5mm thick at 1200mm center to center distance along with GI Cleat & Steel Expansion Fasteners.</p> <p>The Ceiling section of 0.5mm thickness having curled wedge of 51.5mm and two flanges of 26mm each with lips of 10.5mm at 450mm c/c. along with connecting clips of 12.5mm drive fixed with sheet metal screws at 230mm c/c. <u>METAL GRID INSTALLATION</u>: - Perimeter channel fixed to all side of walls, partitions, beams, columns, whichever applicable fixed with sheet metal screws with rawalplugs at 225mm center to center & intermediate channels at 1200mm center to center including GI steel hangers fixed to the slab, beams soffit, whichever with GI cleats & steel expansion fastners.soffit, whichever with GI cleats & steel expansion fastners.</p> <p>The ceiling section placed in a direction perpendicular to the intermediate channel at 450mm c/c. fixed to the intermediate channel with the help of connecting clips & 12.5mm dry wall Sheet Metal Screws at 230mm c/c. Distance.</p> <p><u>COVERING</u>: - Fixed 12.5mm thick gypsum board to the metal frames in required shape in taper / square edges of the gypsum board shall be finish with filling the joints with fibre tape finish the surfaces in one level & line finish with three coats of approved make / shade Plastic Emulsion paint including making grooves, cutouts for Light Fittings, AC Grills, AC Diffusers, Smoke Detectors, Sprinklers System, Security System etc. as per the other vendors requirements along with additional frame for Light Fittings & AC Grills, scaffolding etc. complete as per instructions of Architect. <u>OR</u> do as per Manufacturer's Specification.Cutouts will not be deducted while measuring the ceiling area.</p>				
	<u>Mode Of Measurement</u> - Length X Width	1420.00	SFT		
RATE IN WORDS					
E02	<p>GYPNUM VERTICAL DROP (1" HT)</p> <p>Do as above item No. E01, but Providing & fixing gypsum for verticle drop (1') ceiling for the provision of cove light including appd. color paint etc.</p>				

	complete as per instruction of Architect / Engineer. Mode Of Measurement - Per Running Feet	185.00	RFT		
RATE IN WORDS					
E03	GYPSUM VERTICAL DROP (4" HT) Do as above item No. E01, but Providing & fixing gypsum for verticle drop (4") ceiling for the provision of cove light including appd. color paint etc. complete as per instruction of Architect / Engineer. Mode Of Measurement - Per Running Feet	215.00	RFT		
RATE IN WORDS					
E04	GYPSUM PUNNING Providing & Applying 12mm to 15mm thick plaster of paris at the required position on the existing single coat plaster by removing neeru & making rough surfaces. Gypsum make plaster of paris finish with proper leveling including turpentine, scaffolding, cleaning the floors, fittings, fixtures, furniture's etc. complete as per instruction of Architect / Engineer. Mode Of Measurement - Length X Height	645.00	SFT		
RATE IN WORDS					
E05	MODULAR FALSE CEILING Providing & Fixing mineral fibre board false ceiling of AMF / ARMSTRONG or equivalent false ceiling system (THERMATEX FEINSTRATOS MICRO PERFORATED with FINELINE of 15mm GRID with Black GRID REVEAL) of grid size 600mm X 600mm with G.I. ceiling frame work as per Manufacturer's specifications including filling of Acoustic ceiling tiles 15mm thick of size 600mm X 600mm microlook having 0.55 NRC, 38dB & 95% RH and 90% Light Reflector. Smoke Development - 0% Fire Resistance - 120 Minutes A2-s1, d0 & DIN EN 13501-1 The cost of include the cost of frame work for fixing light fixtures. The light fixtures shall not be fixed directly on to the tiles. Complete in all respects as per detail drawings and instructions of Architect. Cutouts will not be deducted while measuring the ceiling area. Mode Of Measurement - Length X Width	725.00	SFT		
RATE IN WORDS					
E TOTAL OF FALSE CEILING					
{F}	STORAGES				
F01	FULL HEIGHT STORAGE - LAMI. (450 MM DEEP) Providing & Fixing full height storage 450mm deep made out of 25mm thick BWR (IS 303) ply frame work for sides, bottom, shelves, top, shutters, 6mm thick BWR ply for backside of storage along with teak wood edge bedding, 40mm X 25mm laminate matching color edge moulding & stainless steel pin for adjustable shelves fixing etc complete. All exposed surfaces shall have approved make/color 1.0mm thick solid core laminate including edges, grooves and 0.8mm thick white colour laminate to all internal surfaces along with necessary approved make/design hardware i.e. Haffle /				

	hettich / Kich Stainless Steel Hinges with Stainless Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade),Stainless Steel Brush Finished Handles, 150mm Stainless Steel Tower bolts at top and Bottom Magnetic Ball Catches, Apporved make locks etc. complete as per detaildrawing and instructions of Architect.				
	<u>Mode Of Measurement - Length X Height</u>	100.00	SFT		
✗ RATE IN WORDS					
F02	LOW HEIGHT STORAGE - LAMINATE Providing & Fixing low height storage 450mm deep made out of 19mm thick BWR ply frame work for sides, bottom, shelves, top, shutters, 6mm thick BWR ply for backside of storage along with teak wood edge beading. All exposed surfaces shall have approved make/color 1.0mm thick solid core laminate including edges, grooves & 0.8 mm thick white color laminate to internal surfaces along with necessary approved make hardware i.e. Haffle / hettich / Kich Stainless Steel Hinges with Stainless Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade), Stainless Steel Brush Finished Handles,150mm Stainless Steel Tower Bolts at top & bottom, Magnetic Ball Catches, Locks, carting away debris out of compound, cleaning the site etc. complete as per site requirements, detail drawing and instructions of the Architect.				
	<u>Mode Of Measurement - Length X Height</u>	65.00	SFT		
✗ RATE IN WORDS					
F03	ABOVE STORAGE (WALL HUNG) Do as above ITEM NO.F02 (Low Height Storage)but storage will be of 1'-6" in depth. storage shall have pelmet made out of 19mm thick BWR ply with approved make / color 1.00mm thick laminate finish & 0.8 mm thick white color laminate to all internal surfaces below storage unit etc. complete as per detail drawing and instructions of Architect /Engineer.				
	<u>Mode Of Measurement - Length X Height</u>	15.00	SFT		
✗ RATE IN WORDS					
F04	SHUTTER BELOW PANTRY Providing and Fixing shutters Below for pantry including bottom & sides made out of 19mm thick BWR ply with edge beading along with 50 mm x 25 mm Aluminium tubular section framework at top & bottom and verticles including approved make. All exposes surfaces shall have approved make/color 1.0 mm thick PVC laminate and 0.8mm thk. approved color laminate from inside surfaces including approved make / design i.e.Blum/ Haffle / hettich / Kich S. S. Hinges , Stainless Steel Brush Finish Handles, 150mm Stainless Steel Tower Bolts at top and bottom, Magnetic Ball Catches,Locks, etc. complete as per site requirements, detail drawings and instructions of the Architect/ engineer.				
	<u>Mode Of Measurement - Length X Height</u>	15.00	SFT		
✗ RATE IN WORDS					
F05	STORAGE FOR ELECTRICAL PANEL				

	<p>Providing and Fixing shutters for electrical panel made made out of 19 mm thick BWR ply with edge beading.</p> <p>All exposes surfaces shall have approved make/color 1.0mm thick solid core laminate and 0.8mm thk. approved color laminate from inside along with 150mm wide Aluminum powder coating A.C.grill at top and bottom for exhaust including approved make/designhardware i.e. S. S. Hinges with S.Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade), Stainless Steel Brush Finish Handles,150mm Stainless Steel Tower Bolts at top and bottom, Magnetic Ball Catches,Locks, etc. complete as per site requirements, detail drawings and instructions of the Architect.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	35.00	SFT		
X RATE IN WORDS					
F TOTAL OF STORAGES					
{G}	SUNDRIES				
G01	<p>PLASTIC EMULSION PAINT</p> <p>Removing the existing color wash/distemper/oil bond distemper / plastic/ luster etc. paint by scrapping, washing and scrubbing. The surface shall then be allowed to dry for atleast 24 hours. It shall be then sand papered to give a smooth & even surface. Holes shall be filled with BIRLA putty made of plaster of paris. Then first coat of primer to be applied.</p> <p>After this necessary leveling shall be done with putty and second primer coat shall be applied. The plastic emulsion paint of approved shade and make shall be applied in minimum 3 coats (finishing paint) including scaffolding,cleaning the floors, fittings, furniture's, ladders, glasses, removing of debris out of the compound etc. complete as per site requirements, detail drawings and instructions of the Architect.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	1500.00	SFT		
X RATE IN WORDS					
G02	<p>ZEBRA BLIND</p> <p>Providing and fixing Zebra Blinds of Approved make / Approved fabric fixed with Aluminium powder coated Head rail along with Stainless Steel drive Rod OR fixed as per Manufacturer's Specification etc. complete as per site requirement and instructions of Architect.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Width</p>	55.00	SFT		
X RATE IN WORDS					
G03	<p>3M GLASS FIME</p> <p>Cleaning & wiping glass surface free of any dust or foreign bodles & then fixing plain frosted film of LUNAR or 3M or equivalent make on a GLASS partition of Abstract Design with warranty as per the Manufacturer Specification. Cost inclusive of cutout, design etc. as per pattern in detail drawing or as per instructions of the Architect.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	150.00	SFT		
X RATE IN WORDS					
G TOTAL OF SUNDRIES					
TOTAL OF "A" TO "G"					
GRAND TOTAL					

GST WILL BE EXTRA