

## PRICE BID

**BOQ : Interior Decoration and Furnishing work : BRANCH INSIDE FURNITURE WORK of SBI SECTOR 10B  
BRANCH, 1ST FLOOR, GANDHINAGAR.**

Sr. No.	Description	Quantity	Unit	Rate	Amount
<b>Note :</b>	<b>Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills</b>				
<b>1</b>	<b>SINGLE WINDOW COUNTER / CASH COUNTER SIZE 5'-0" X 2'-6" with White corian &amp; blue lacquered glass finishing</b>	9.15	RMT		
	Supplying, fixing and keeping in position single window counter complete as per design and drawing, made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. C.P. Teak wood lipping on all edges wherever required.				
	The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit with 18 mm thick commercial plywood and with approved make multipurpose Auto Lock in drawer and shelf unit. The cost shall also be inclusive of the following.				
[a]	size :				
	Description: L B Ht.				
	Writing Top 5'-0" 2'-6" 2'-6"				
	4 Drawers with				
	pigeon hole 2'-0" 1'-3" 2'-0"				
	P/f supplying metallic cable manager system with nessessory cutout in top surface & keyboard tray with mouse pad made from CRCA steel duly powder coated. It must have Built in slide which must have soft palmrest and stowaway design. Mouse pad mounted underneath it.				
[b]	Working table top and edges shall be finished with 6 mm thick white corian of DUPONT or equivalent approved make as per drawing and direction with all labour and material.				
[c]	Front Apron : 2 nos 6 mm thick flexy ply wood in round shape with 6 mm thick white corian shall be provided at front as per design. All edges should be finished with corian of DUPONT make.				
[d]	Front pannel shall be finished with 6 mm thick 18" high blue back painted glass of approved make and fixed on 18 mm thick commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per drawing				
[e]	Foot rest of 3" x 1.5" in C.P. Teak wood and CPU stand of 18 mm ply finished with 1 mm thick laminate of size 16" x 24"				
[f]	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.				
[g]	All fittings like S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make.				
[h]	Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.				
[i]	<b>All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade etc. complete</b>				
[j]	Counter shall be made independent in Length of 5'-0" and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	<b>FINISHING DETAILS IN NUTSHELL:</b>				
	1) Table Top : 6 mm thick white corian				
	2) <b>Front Apron:</b> Round corian and 6 mm thick backpainted blue glass fixed with Natural Silicon				
	3) <b>Facing of Drawers:</b> 1.00 mm thick laminate finish				
	4) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
<b>1.1</b>	<b>SWO TABLE CURVED FRONT FACIA ON COLUMN IN BETWEEN SWO TABLES. SIZE 5'-6" L X 6" W with White corian &amp; blue lacquered glass finishing.</b>	1.7	RMT		
	<b>Item is excluding working top and front 12mm toughen glass partition, drawers, key board tray, side unit and partition.</b>				
	Supplying, fixing and keeping in position swo table's ONLY FRONT CURVED SHAPE PART on CNC panelled Column as per design and drawing, made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. with White corian & blue lacquered glass finishing.				
	Front Apron : 2 nos 6 mm thick flexy ply wood in round shape with 6 mm thick white corian shall be provided at front as per design. All edges should be finished with corian of DUPONT make.				
	Front pannel shall be finished with 6 mm thick 18" high blue back painted glass of approved make and fixed on 18 mm thick commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per drawing				
	Counter Curved shape part shall be made independent in Length of 5'-6" and properly placed between two partitions of inline swo tables and back side column. Counter will be measured in RMtr between two partition and paid.				
<b>1.2</b>	<b>Providing and fixing 12 mm thick Toughened Glass partition on counter top, front side as follows.</b>	7	SQMT		
	Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. All edges of glass shall have Diamond cut polished edges as directed.				
<b>1.3</b>	<b>Providing and fixing Round Shape 12mm thick Toughened float Glass partition between Single Window counters as follows.</b>	3	SQMT		
	12 mm thick Toughened clear float glass with polished edges shall be fixed with silicon and T.W beading support on wooden partition as directed. All edges of glass shall be Diamond cut polished edges as directed complete. Wooden partition will be paid seperately. Maximum length and height will be measured for payment purpose.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
<b>2</b>	<b>TABLES</b>				
<b>A</b>	<b>OFFICER &amp; CLERK TABLES</b>				
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick commercial ply wood with 1.00 mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Storage cabinet of 1'-3" x 2'-0" x 2'-6" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make , grouplock, S.S. Handle. Computer Key board of metal of approved make shall be provided. Foot rest of 1 1/2" x 3" T.W members shall be provided. All internal surface will have 0.60 mm thick balacing laminate.				
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1.00 mm laminate Finish & groove pattern.				
	Table side made from 18 mm thick ply wood with 1.00 mm thick laminate finish shall be provided in a pattern.				
	Drawer Fascia made out of 18 mm thick Plywood. The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood. fixing 1.00 laminate on front side and all the internal surfaces shall be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. etc complete as directed.				
	Table shall have stand for keeping CPU and metallic cable Manager shall be provided in table top. All exposed edges of plywood shall have laminate with smooth edges & corners.				
	Exposed edges of Table Top, Leg panel & Side Shelf shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.				
	All the edges without laminate / balancing laminate shall be paint of approved shade.				
2.1	Loan head Table Size: 5'-6"x2'-6"	1	NO		
2.2.	Officer Table Size: 5'-0"x2'-6"	17	NO		
2.3	Clerk Table Size: 4'-6"x2'-6"	4	NO		
<b>B</b>	<b>AGM TABLE</b>				
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick commercial ply wood with table top & all around edges 6 mm thick Corian (approved shade by architct) with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Storage cabinet of 1'-6" x 2'-0" x 2'-6" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make , grouplock, S.S. Handle. Computer Key board of metal of approved make shall be provided. Foot rest of 1 1/2" x 3" T.W members shall be provided. All internal surface will have 0.60 mm thick balacing laminate.				
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1.00 mm laminate Finish & groove pattern.				
	Table side made from 18 mm thick ply wood with 1.00 mm thick laminate finish shall be provided in a pattern.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	Drawer Fascia made out of 18 mm thick Plywood. The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood. fixing 1.00 laminate on front side and all the internal surfaces shall be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. etc complete as directed.				
	Table shall have stand for keeping CPU and metallic cable Manager shall be provided in table top. All exposed edges of plywood shall have laminate with smooth edges & corners.				
	Exposed edges of Table Top, Leg panel & Side Shelf shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.				
	All the edges without laminate / balancing laminate shall be paint of approved shade.				
2.4	AGM Table size 8'-0"x 3'-0"	1	NO		
<b>C</b>	<b>SUB STAFF TABLE</b>				
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick commercial ply wood with 1.00 mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Foot rest of 1 1/2" x 3" T.W members shall be provided. All internal surface will have 0.60 mm thick balacing laminate.				
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1.00 mm laminate Finish.				
	Table side made from 18 mm thick ply wood with 1.00 mm thick laminate finish.				
	All exposed edges of plywood shall have laminate with smooth edges & corners.				
	Exposed edges of Table Top, Leg panel shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.				
	All the edges without laminate / balancing laminate shall be paint of approved shade.				
2.5	Table Size: 5'-6"x2'-0"	1	NO		
3	<b>GRAHAK MITRA TABLE OF 2'-3" WIDE with PU coating finish</b>	2.15	RMT		
	Same as above item no 2 but Size 2'-3" wide with storage unit in Table with 4mm thick MDF board + Blue and white PU Coating finishing on all exposed visible surface as per drawing and instruction of Architect/Bank For Grahak Mitra/Tech Mitra (Help Desk Table)				
	Table top made from 18 mm thick ply wood + 4mm thick MDF board with PU coating finish				
	Apron (Front side) made from 18 mm thick ply wood + 4mm MDF board with PU Coating finish				
	Both sides made from 18 mm thick ply wood + 4mm MDF board with PU Coating finish				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	3" thick Partition above working table top made from 18 mm thick+6 mm thick ply wood with necessary framing with 4mm thick MDF board + PU Coating finish as per drawing.				
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	Drawer Storage Unit- 1'-4" W x 2'-0" D, 2 Nos Drawer on top and rest 1 No shutter				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
	<b>(FOR DETAILS REFER DRG. NO-6)</b>				
	<b>FINISHING DETAILS IN NUTSHELL:</b>				
	1) <b>Table Top</b> : 18 mm Thick Plywood with 4 mm thick MDF with High gloss white PU Coating				
	2) <b>Front Apron &amp; Sides</b> : 4mm thick MDF with High gloss white/blue PU Coating				
	3) <b>Facing of Drawers</b> : 1.0 mm thick Laminate finish				
4	<b>CUSTOMER WRITING DESK</b>	1	NO		
	Writing Desk Size 4'-0" L x 1'-3" x (0'-6"+3'-0") ht.				
	Verticle Sides and bottom shall be made out of 36 mm (2X18) thick Commercial plywood and back side 12 mm thick ply wood with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Toughend glass with polished edges making different divisions by 18 mm thick glass / plywood with laminate on both side for slips or forms as per detail drawing and inststruction complete. including provding storage shutter below glass top. (Drawing as enclosed herewith) Laminate to be provided on all visible surface [REFER DRG ]				
5	<b>STORAGE CABINET</b>	48.5	SQ.MT		
	Supplying and installation Storage cabinet for keeping computer and printer of size 1'-3"/1'-4" width 2'-6"/3'-0" height having openable shutters as directed. Cabinet shall be made from 18 mm thick commercial ply wood with 1.00 mm thick laminate Finish. Back shall be made from 6 mm thick commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with 1mm laminate finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing computers. All the internal surface, back side shall have 0.60 mm thick balacing laminate. Only Front elevation shall be measured for payment purpose.				
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
5.1	<b>For SWO side unit &amp; AGM side unit &amp; back storage</b> Same as above item No-7 but Side Table Top and edges shall be finished with 6 mm Thick Corian on Top and Edges. All other visible surface shall be finished with 1.00 mm th laminate. With openable shutter as directed. Only Front elevation shall be measured for payment purpose.	7.5	SQMT		

Sr. No.	Description	Quantity	Unit	Rate	Amount
6	<b>P/F ELECTRIC CUB BOARD</b>	4	SQMT		
	Providing and fixing Electric cup board using 18 mm thick Bison board for inside verticle division, shelves and shutter. Aluminium framing of 50x25x1.20mm thick with 6 mm thick Bison board on both side for outer partition with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamel paint on all internal surface. Shutter will have approved make lock, handle, hinges, ball catches & S.S Perforated jali etc.complete as directed. Depth of cup board will be around 1'-3". Height of shutter will be maximum 7'-0". Only Front elevation shall be measured for payment purpose.				
	<b>LOW HEIGHT PARTITION WORK</b>				
7	<b>P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION FOR BACK SIDE AND IN BETWEEN S.W COUNTER AND CASH CABIN WITH TOUGHENED GLASS</b>	18.4	SQMT		
	Providing and fixing low height partition using 50mm x 25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides, fixing 12 mm thick transparent toughened glass as directed. Applying polish on exposed steam beach members with lacquer polished edges as directed. Laminate to be provided only on visible surface.				
	<b>For Low height Single window and Cash cabin partition, Average height of partition shall be measured and paid.</b>				
7.1	<b>PROVIDING AND FIXING WICKET GATE WITH BOTH SIDE LAMINATE</b>	8.4	SQMT		
	Same as item no 10 but P/F 30 / 32 mm thick flush shutter with both side laminate including SS hinges with countersunk SS screws, Approved make Night latch Lock, S.S Handles,Door stoppers, doorstep etc complete as directed.				
7.2	<b>P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION WITH CLEAR FLOAT GLASS</b>	61.7	SQMT		
	Providing and fixing low height partition using 50mm x25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides. Fixing 12mm thick free clear float glass as directed. Applying lacquer polish on exposed steam beach members / edges as directed. Laminate to be provided only on visible surface Providing pinup board of soft board covered with fabric and fixed in partition as per design/instruction complete as directed.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	<b>FULL HEIGHT PARTITION WORK</b>				
8	<b>P/F BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED FULL HEIGHT PARTITION WITH DOOR</b>	109	SQMT		
	Providing and fixing both sides laminate full height partly glazed partition using 50mm x 25mm x 1.50mm thick Aluminium members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply on both sides, 1.0 mm laminate of approved make shall be fixed on MDF / plywood. Providing and fixing 5.0/8.0 mm thick float glass as directed in the partition. Providing and fixing door shutter using 32 mm thick flush shutter both side laminated and fixing 6 mm thick glass with beading patti, 5" Long 3 Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall be provided in door shutter. All visible members if not laminated shall have lacquer polished as directed.[REFER DRG NO]				
	For purpose of payment partition height up to bottom of false ceiling only shall be measured and paid . No extra payment shall be made for members going up to slab/beam bottom.				
8.2	<b>Providing and fixing Isolated flush door shutter (Partly Glazed and Partly Laminate) with frame as follows.</b>	3.5	SQMT		
	Providing and fixing 4"x2" steam beach member for frame and Flush door shutter made out of 32 mm thick flush door with 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading, 32 x 12 mm thick steam beach periphery patti around shutter edges, 1 mm thick laminate on both sides, 35x12mm thick steam beach stopper patti on frame including 3 Nos 5" long SS hinges with countersunk S S screws, Approved make Dead Lock, S.S Handles, 150 mm long Door stoppers, doorstop of approved make etc. All exposed surface /edges not laminated be provided with lacquer polish. Work to be completed as per drawing & instructions [REFER DRG NO]				
	<b>GLASS DOORS AND PARTITIONS</b>				
9	<b>P &amp; F FULLY GLAZED DOOR WITH PATCH FITTINGS for Main Entrance Door For Branch &amp; ATM</b>	4.5	SQMT		
	Providing & Fixing fully glazed main door at the main entrance and ATM. The Item includes fixing of <b>12 mm th. Toughened glass</b> with the help of <b>top patch &amp; bottom patch fittings</b> . The door will have patch lock, ptl pivot, 100 Kg floor spring & 25mm dia D shape 400 mm long handles both sides, <b>(Ozone Make OGH-55P11-25X400)</b> , fixed with the glass by making necessary cutouts & holes. The glass edges shall be polished on all sides. The entire door shall be erected in complete line & level. The door will have S.S brush finish Signage for pull & push.				
	The patch fittings (Ozone make) shall be of aluminium with s,s, matt finish coating & signage shall be of kich make. The entire door complete in all respect should be installed in positions as required.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	<b>PANELLING WORK</b>				
10	<b>P/F Wall panelling with laminate finishing for wall and Pillar etc</b>	45	SQMT		
	Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect. .				
10.1	Providing and fixing 8mm thick MDF Board exterior grade with jali work with high gloss PU coating over central column having 8mm thick MDF Board Exterior grade covered with 1 mm thick blue glossy laminate fixed on pillar with aluminium framing of 25mm x25mm x1.20 mm thick at maximum 2'-0" c/c bothway as per drawing and direction with all labour and material etc complete <b>(Rate shall be including CNC cutting jali work and 1 mm thick blue glossy laminate behind design jali work as directed)</b>	50.5	SQMT		
10.2	<b>Panelling for Digital wall with Blue / white high gloss PU Coating finishing</b>	11.6	SQMT		
	Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface front area shall be measured for payment.				
10.3	<b>P/A WALL PAPERS on Digital wall, BM &amp; AGM Wall</b>	12.6	SQMT		
	Providing and applying <b>Wall paper</b> approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft				
11	<b>SOFT BOARD</b>	8.5	SQMT		
	Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.				
12	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure.	15	NO		
	<b>FALSE CEILING WORK</b>				
13	<b>P/F GYPSUM BOARD FALSE CEILLING</b>	540	SMT		
	Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section <b>of Gypsteel ULTRA ( Gypsteel Ultra, Shera brand shall be used)</b> supporting system in line and level. Finishing the surface and <b>applying 3 coats of Plastic emulsion paint</b> as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India.				
	<b>After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.</b>				



Sr. No.	Description	Quantity	Unit	Rate	Amount
	<b>Note : (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in Rmt and paid in SqM (3) Only finished visible surface area shall be measured for payment.</b>				
13.1	Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceiling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid	210	SMT		
	Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. <b>Cutout for light and Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose</b>				
	After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications				
13.2	<b>Wpc Fluted Panel Ceiling</b>	16	SMT		
	For AGM & VIP Waiting area				
	Providing and fixing WPC fluted panel on 12 mm thick plywood with necessary supporting accessories & high adhesive bond/fevicol Hitex bond in line and level.				
14	<b>Sofa</b>	25	RMT		
	Providing and fixing sofa as per Description below : The basic structure of sofa shall be made of solid wood members with flat spring and 12mm thick Commercial Ply (OIS: 303) and wooden frame. It shall be made out of 100mm thick PU foam of 32 densities in seat and back in 75mm thick rubber foam with 25mm thick high density PU foam rounded as per design with approved 48" to 54" wide upholstery fabric of Rs 600/- per meter complete as per design and instructions from engineer-in-charge.				
14.1	<b>EXISTING SOFA RENOVATION</b>	26	RMT		
	Reconditioning of existing sofa by changing Upholstry of Rs. 650 per Rmt. to be provided. Work also involve replacing back cloth and any broken wooden members & foam, complete lacquer polishing as directed.				
15	<b>P/F PANTRY PLATFORM STORAGE UNIT SHUTTER</b>	3	SMT		
	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk plywood with 1.0 mm laminate for shutters. Providing 1/2" Tk. T.W beading all around shutter. 18mm ply. to be used for internal shelves. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All invisible surface shall be painted with minimum 2 coats of premium 1st quality paint on the inner side of approved shade as directed.				
16	<b>ROLLER BLIND</b>	23	SMT		
	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 1400 Per Sq.Mtr excluding GST)				
	Brief list of make are as under or any equivalent make will be permitted by Engineer incharge.				
	Roller Blid- Vista wall fashion / Mac or equivalent				

Sr. No.	Description	Quantity	Unit	Rate	Amount
17	<b>Supplying and installation 1'-9" x 1'-9" x 1'-3" height Center Tepoy as follows.</b>	7	NOS		
	Providing and making open box structure type Tepoy made out of 36 mm (2X18) thick plywood with all over 1.0 mm thick laminate finish provided with bevelled & diamond polished edges 12mm thick glass top supported on 75 mm X 25 mm SS studs complete as directed.				
	<b>TOTAL COST "A"</b>				
<b>Note:</b>					
[a]	In all furniture work, contractor shall make necessary cutout in panelling/partitions / wooden members to facilitate electrical/data cabelling and No extra amount shall be paid for this				
[b]	All internal surface (non visible surfaces) shall be provided with the 0.60 mm thick balacing laminate of aproved make & shade in the all S.W Counters/Tables/ Credenza,Storage Cup Board etc.				

Note : GST as applicable will be paid extra.