BILLS OF QUANTITIES FOR PROPOSED INTERIOR FURNISHING WORK (LOOSE & FIXED FURNITURE) OF STATE BANK OF INDIA FOR KASINDRA BRANCH DIST. AHMEDABAD SN Description Quantity Unit Rate Amount Note: Rate should be inclusive of material, labour, tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills. **FURNISHING WORK** Note : for all work stations FINISHING DETAILS IN NUTSHELL: 1) Table Top: 6 mm thick white corian 2) Front Appron: Round Corian and 6 mm thick blue lacquered glass fixed with Natural Silicon 3) Facing of Drawers: 1.00 mm thick laminate finish The W.S. should have Ready Made Foot Rest. High impact polysterene with crome plated metal structure of approved make There should be provision for cable manager(Metal Cable Manager) system with necessary cutouts in top surface C.P.U. trolly with castors/roller supports/ Nylon castors. Key board tray with mouse pad made from CRCA steel duly powder coated. It must have built-in slides which, must have a soft palm rest and a stow-away design of mousepad mounted underneath it. All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade etc. complete Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers. SINGLE WINDOW COUNTER / CASH COUNTER SIZE 5'-0" X 6.10 **RMT** 2'-9" with White corian & blue lacquered glass finishing Supplying, fixing and keeping in position single window counter complete as per design and drawing made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. C.P. Teak wood lipping on all edges wherever required. The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit with 18 mm thick commercial plywood and with approved make multipurpose Auto Lock in drawer and shelf unit. The cost shall also be inclusive of the following. [a] size: В Н Description: 5'-0" 2'-9" 2'-6" Writing Top 4 Drawers with 1'-3" 2'-0" 2'-0" pigeon hole 3'-0" x 1'-4" x 2'-6" x 4 Nos Side Crdenza Side Credenza(Side Rack/Storage):For S.W Countwer Same as above item but Side Table Top and edges shall be finished with 6 mmThick White Corian on Top and Edges. All other visible surface shall be finished with 1.00 mm th laminate. Size shall be 3'-0"x 1'-4"x2'-6" ht. With openable shutter as directed Providing and fixing 12 mm thick Toughened Glass partition on counter top, front side as follows. The counter will have additional 1 no. 12 mm th. Clear toughten glass of size: 5'-0"x 2' 6" with one number half round cutout for cash transaction and one number circlualr cutout (5" dia) for communication fixed with side partition with S.S. bracket (for four counters)

SN	Description	Quantity	Unit	Rate	Amount
[b]	Working table top and edges shall be finished with 6 mm thick				
	white corian of DUPONT or equivalent approved make as per drawing and direction with all labour and material.				
[c]	Front Appron: 2 nos 6 mm thick flexy ply wood in round shape				
	with 6 mm thick white corian shall be provided at front as per				
	design. All edges should be finished with corian of DUPONT make.				
[d]	Front pannel shall be finished with 6 mm thick 18" high blue				
	lacqured glass of approved make and fixed on 18 mm thick				
	commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per				
	drawing				
[e]	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.				
[f]	All fittings like S.S. handle, Auto Lock to each drawer and				
	cabinet doors, piano / auto hinges, ball catcher, stopper, metal				
[g]	cable manager etc. should be fixed of approved make. Counter shall be made independent in Length of 5'-0" and				
[9]	properly placed between two partitions. Counter will be				
	measured in RMtr between two partition and paid.				
2	Providing and fixing 12mm thick Toughened float Glass				
	diapharm partition between Single Window counters as follows.	0.90	SQMT		
	12 mm thick Toughened clear float glass with polished edges				
	shall be fixed with silicon and T.W beading support on wooden				
	partition as directed. All edges of glass shall be Diamond cut polished edges as directed complete. Wooden partition will be				
	paid seperately. Maximum length and height will be measured				
	for payment purpose.				
3	TABLES				
Ů	TABLES				
	Note : for all work stations				
	FINISHING DETAILS IN NUTSHELL: 1) Table Top: 1.0 mm thick Dark laminate & Burma Teak				
	beading on Edges with polished				
	2) Front Appron & Sides: 1.0 mm thick Dark Laminate				
	3) Facing of Drawers: 1.00 mm thick laminate finish The W.S. should have Ready Made Foot Rest. High impact				
	polysterene with crome plated metal structure of approved make.				
	There should be provision for cable manager(Metal Cable				
	Manager) system with necessary cutouts in top surface				
	C.P.U. trolly with castors/roller supports/ Nylon castors.				
	Key board tray with mouse pad made from CRCA steel duly powder coated. It must have built-in slides which, must have a				
	soft palm rest and a stow-away design of mousepad mounted				
	underneath it.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick halancing laminate of approved shade etc.				
	with 0.60 mm thick balancing laminate of approved shade etc. complete				
	Heavy duty telescopic full extension sliding channel of approved				
	make shall be used in all drawers.				

SN	Description	Quantity	Unit	Rate	Amount
ЗА	MANAGER TABLE SIZE: 6'-0" X 2'-9" X2'-6" HT. with Side Credenza & Laninate finish on Table Top , sides and all		NO		
	Other visible surfaces etc complete as follows Supplying and installation of Table as per the following description: Size 6'-0" x 2'-9". Table top shall be made from 18 mm thick commercial ply wood with 1.0 mm thick Laminate with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Drawers of size of 1'-3" x 2'-0" x 2'-6" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make, grouplock, S.S. Handle. Ready made metal Key board with mouse pad of approved make shall be provided. Exposed surfaces of darwers shall have laminate, All internal surface will have 0.60 mm thick balacing laminate				
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with laminate as per drawing Table side made from 18 mm thick ply wood with 1.0 mm thick Laminate finish shall be provided in a pattern as per drawing. Laminate to be provided on all visible surfaces.				
	Drawer Fascia made out of 18 mm thick Plywood. The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood. fixing laminate on front side and all the internal surfaces shall be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. All the edges of Drawer Fascia be provided with teak wood edge bending with laqueer polished etc complete as				
	Table shall have stand for keeping CPU and metalic cable Manager shall be provided in table top. All exposed edges of teak wood shall have polished with smooth edges & corners				
	Exposed edges of Table Top, Leg panel & Side Shelf shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.				
	All the surface without laminate / balancing laminate shall be lacquered polished of approved shade Side Credenza Size 3'-3"x1'-4" x 2'-6"/3'-0" ht. Openable shutter with 1.00 mm thick Laminate finish on Top , front, sides, shutter and 35 mmx6 mm thick Burma Teak beading on Top Edges. Laminate to be provided only on visible surface etc complete as follows. Only Front elevation will be measured for payment purpose. (For BM) Rate for length Less then 3'-3"(description Same As Iteam No.6)				
	Supplying and installation side cabinet for keeping computer and printer of size 1'-4" width 2'-6" height and 3'0"/3'-3" length having Partly Drawers & Partly openable shutters as directed. Cabinet shall be made from 18 mm thick commercial ply wood with 1.00 mm thick Laminate Finish. Back shall be made from 6 mm thick commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with laminate finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing Exposed edges of Sides, Table Top shall be made 36 mm thick				
	by providing additional 18 mm thick ply wood patta of required width. All the internal surface (non visible surface) shall be provided				
	with 0.60 mm thick balancing laminate				

SN	Description	Quantity	Unit	Rate	Amount
	·	-			
	FINISHING DETAILS IN NUTSHELL:				
	Top : Dark Laminate & Burma Teak beading on Edges with pilishade				
	2) Front Appron & Sides: Frosty White Laminate				
	As per drawing and instruction of Architect/Bank work to				
	be Completed (FOR DETAILS REFER DRG. NO-)				
	, , , , , , , , , , , , , , , , , , , ,				
3B	Same as above Item-no-3 & 3A but Size: 4'-6"x2'-6" with side				
	credenza & with 4 Nos Drawer Unit with 1.0 mm thick Laminate	2.00	NO		
	finish on all exposed surfaces				
4	GRAHAK MITRA TABLE OF 2'-3" WIDE with PU coating	1.40	RMT		
	finish	1.40	IXIVII		
	Same as above item no 2 but Size 2'-3" wide with storage unit				
	in Table with 4mm thick MDF board + Blue and white PU Coating finishing on all exposed visible surface as per drawing				
	and instruction of Architect/Bank For Grahak Mitra/Tech Mitra				
	(Help Desk Table)				
	Table top made from 18 mm thick ply wood + 4mm thick MDF				
	board with PU coating finish				
	Apron (Front side) made from 18 mm thick ply wood + 4mm				
	MDF board with PU Coating finish				
	Both sides made from 18 mm thick ply wood + 4mm MDF board with PU Coating finish				
	3" thick Partition above working table top made from 18 mm				
	thick+6 mm thick ply wood with necessary framing with 4mm				
	thick MDF board + PU Coating finish as per drawing.				
	Exposed edges of Table Top shall be made 36 mm thick by				
	providing additional 18 mm thick ply wood patta of required				
	width.				
	Drawer Storage Unit- 1'-4" W x 2'-0" D, 2 Nos Drawer on top and rest 1 No shutter				
	All the internal surface (non visible surface) shall be provided				
	with 0.60 mm thick balancing laminate				
	(FOR DETAILS REFER DRG. NO-6)				
	FINISHING DETAILS IN NUTSHELL:				
	1) Table Top: 18 mm Thick Plywood with 4 mm thick MDF with				
	High gloss white PU Coating				
	Front Appron & Sides: 4mm thick MDF with High gloss white/blue PU Coating				
	3) Facing of Drawers: 1.0 mm thick Laminate finish				
	of the state of th				
5	CUSTOMER WRITING DESK	1.00	NO		
	Writing Desk Size 3'-0" L x 1'-3" x (0'-6"+3'-0") ht.				
	Verticle Sides and bottom shall be made out of 36 mm (2X18)				
	thick Commercial plywood and back side 12 mm thick ply wood				
	with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Thoughend glass				
	with polished edges making different divisions by 18 mm thick				
	glass / plywwod with laminate on both side for slips or forms as				
	per detail drawing and inststruction complete. (Drawing as				
	enclosed herewith) Laminate to be provided on all visible				
	surface)				

SN	Description	Quantity	Unit	Rate	Amount
6	STORAGE CABINET (LHS) with Top & Front laminate finished. Storage of any height Same as above Item No-3 & 3A, but all external surfaces to be	7.10	SQMT		
	finished with Laminate (approved shades)				
	FINISHING DETAILS IN NUTSHELL: 1) Top: Dark Laminate & Burma Teak beading on Edges with pilishade				
	2) Front Appron & Sides: Dark Laminate/Frosty white Laminate as per design & instructions				
8	P/F ELECTRIC CUB BOARD Providing and fixing Electric cup board using 18 mm thick Bison board for inside verticle division, shelves and shutter. Aluminium framing of 50x25x1.20mm thick with 6 mm thick Bison board on both side for outer partition with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamal paint on all internal surface. Shutter will have approved make lock, handle, hinges, ball catches & S.S Perforated jali etc.complete as directed. Depth of cup board will be around 1'-3". Height of shutter will be maximum 7'-0". Only Front elevation shall be measured for payment purpose. P/F PANTRY PLATFORM CUB BOARD SHUTTER Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk plywood with 1.0 mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All the without lamiante surface shall be polished/ synthetic enamal paint as directed complete.Providing and fixing 0.60 mm thick balancing laminate on internal shutter surface	0.80	SQMT		
	LOW HEIGHT PARTITION WORK				
9	P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION FOR BACK SIDE AND IN BETWEEN S.W COUNTER AND CASH CABIN WITH TOUGHENED GLASS	7.60	SQMT		
	Providing and fixing low height partition using 50mm x 25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides, fixing 12 mm thick transparent thoughened glass as directed. Applying polish on exposed steam beach members with lacquer polished edges as directed. Laminate to be provided only on visible surface [FOR DETAILS REFER DRG. NO-1]				
	For Low height Single window and Cash cabin partition, Average height of partition shall be measured and paid.			_	

SN	Description	Quantity	Unit	Rate	Amount
	•	,			
10	PROVIDING AND FIXING WICKET GATE WITH BOTH SIDE	1.30	SQMT		
	LAMINATE		• • • • • • • • • • • • • • • • • • • •		
	Same as item no 9 but P/F 30 / 32 mm thick flush shutter with				
	both side laminate including SS hinges with countersunk SS				
	screws, Aprroved make Night latch Lock, S.S Handles,Door				
	stoppers, doorstop etc complete as directed.				
	FULL HEIGHT PARTITION WORK				
11	P/F BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED FULL				
	HEIGHT PARTITION WITH DOOR WITH DOOR CLOSURE	27.10	SQMT		
	Providing and fixing both sides laminate full height partly glazed				
	partition using 50mm x 25mm x 1.50mm thick Aluminium				
	members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick				
	MDF Board exterior grade / 6 mm thick ply on both sides,1.0				
	mm laminate of approved make shall be fixed on MDF / plywood.				
	Providing and fixing 5.0/8.0 mm thick float glass as directed in				
	the partition. Providing and fixing door shutter using 32 mm thick				
	flush shutter both side laminated and fixing 6 mm thick glass				
	with beading patti, 5" Long 3 Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall				
	· · · · · · · · · · · · · · · · · · ·				
	be provided in door shutter.Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure. All				
	visible members if not laminated shall have lacquer polished as				
	directed.				
	For purpose of payment partition height up to bottom of false				
	ceilling only shall be measured and paid. No extra payment				
	shall be made for members going up to slab/beam bottom.				
	5 5 1				
12	PROVIDING AND FIXING 12 MM THICK TOUGHENED				
	GLASS DIAPHARM FOR SEPARATING TWO M/C FOR E-	3.30	SQMT		
	LOOBY				
	P /F 12mm th Toughened glass Diapharm between two				
	machines with etching and frosting Films complete as directed.				
	Glass edges shall be round moulded and polished as per direction. Glass shall be fixed in wall and floor with necessary				
	suitable patch fittings as directed. (Area based on outer				
	diameters shall be measured and paid).				
	alamotoro onali po mododrod and palaj.				
	PANELLING WORK				
13	P/F Wall panelling with laminate finishing for wall and	14.40	SQMT		
	Pillar etc	14.40	SUNI		
	Providing and laying panelling on walls & pillars having 12 mm				
	thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th				
	laminate fixed on wall & pillars with Aluminium. framing of				
	25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on				
	wall and pillar etc complete as directed as per design and				
	instruction of Architect				

011	December Com	0	1124	D-1-	A 1
SN	Description	Quantity	Unit	Rate	Amount
14	Providing and fixing 8mm thick MDF Board exterior grade with jali work with high gloss PU coating over central column having 8mm thick MDF Board Exterior grade covered with 1 mm thick blue glossy laminate fixed on pillar with aluminium framing of 25mm x25mm x1.20 mm thick at maximum 2'-0" c/c bothway as per drawing and direction with all labour and material etc complete (Rate shall be including CNC cutting jali work and 1 mm thick blue glossy laminate behind design jali work as directed)	4.40	SQMT		
15	Panelling for Display wall with 3M Vinyl glossy Film with printed design	1.70	SQMT		
	Providing and laying panelling on wall having 8 mm th MDF Board exterior grade with 3M vinyl glossy films with printed design fixed on wall with Aluminium framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways etc. complete as directed. panelling as per design and instruction of Architect. MDF board to be finished with 0.60 mm thick laminate or paint before laying 3M film. Only Front elevation area shall be measured for payment purpose.				
	Exposed edges of Display wall four side shall be made 36 mm thick by providing additional required thickness MDF patta of required width.				
16	6 Panelling for Digital wall with Blue / white high gloss PU Coating finishing		SQMT		
	Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only front elevation surface area shall be measured for payment.				
17	P/A WALL PAPERS on Digital wall	2.50	SQMT		
	Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft				
18	ALUMINUM COMPOSITE PANEL FOR E-LOBBY	57.20	SQMT		
	Providing and fixing 3 mm thick aluminium composite panel of Flexi Bond / Euro Bond / Timex with 0.25 mm foil with 50 mm x 25 mm x 1.20 mm thick aluminium hollow section tray system with minimum 20 mm bending with silicon Dow Coming of GE seal proof - ACP of approved indian make complete as per selection and direction of Architect for front facade for the building. This item will be carried out as per manufacturer's specifications. Rate also includes providing trap door shutter with hinges, stoppers etc complete as directed. Design as per Bank standered Drawing and Architect's instructions etc complete. TIMEX - DIAMOND WHITE - 111, NAVY BLUE - 117 or equivalent				
-	EALSE CEILING WORK				
19	FALSE CEILING WORK	45.10	SMT		
19	P/F GYPSUM BOARD FALSE CEILLING	45.10	SIVII		

SN	Description	Quantity	Unit	Rate	Amount
	Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA (Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India.				
	After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.				
	Note: (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in RMt and paid in SqM (3) Only finished visible surface area shall be measured for payment.				
20	Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceilling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid	70.30	SMT		
	Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. Cutout for light and Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose				
	After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications				
21	SOFT BOARD	1.50	SQMT		
	Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.				
	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 135=00 Per Sq.Ft Excluding GST)	10.90	SQMT		
23	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.	10.00	SQMT		
24	Supplying and installation Dressing Table with Puffy as follows.	1.00	NO		

SN	Description	Quantity	Unit	Rate	Amount	
	Dressing Table shall have 1'-6" x 4'-0" size 5mm thick mirror with					
	1 1/2" x 3" T.W frame and 12 mm thick BWR plywood 2'-0" x 6"					
	size with 1 mm thick laminate on top and having polished edges					
	/ bottom supported by brass bracket 2 Nos. as directed.					
	Puffy shall be made of using TW member of size 2"x2" and 18					
	mm th.plywood for seat support. Seat shall be padded with 4"					
	foam covered with hession cloth and upholstered with Approved					
	shade and quality fabric. Basic price of fabric shall be Rs.400					
	per Rmt. Visible wooden support shall be polished. Size of Puffy					
	shall be 1'6"x1'6".					
25	Supplying and installation 3'-0" x 1'-9"x 1'-3" height Center	1.00	NO			
	Tepoy as follows. Providing and making open box structure type Tepoy made out					
	of 36 mm (2X18) thick plywood with all over 1.0 mm thick					
	laminate finish provided with bevelled & diamond polished edges					
	12mm thick glass top supported on 75 mm X 25 mm SS studs					
	complete as directed.					
	·					
26	Same as above but size 1'-9" x 1'-9" x 1'-3" height for	1.00	NO		_	
	Corner Tepoy	1.00	.,0			
	TOTAL COST "A"					
	SAY					

(SIGNATURE OF TENDERER/FIRM) (SEAL OF FIRM)
PLACE:
NAME OF TENDERER DATE:

Tender Amount(In Words) Rupees: