## PRICE BID FOR INTERIOR FURNISHING WORK FOR STATE BANK OF INDIA BRANCH AT RAIPUR RANI S.No Quantity Unit Description Rate Amount PANELING/PARTITON Note: For the Paneling, Full height partitions and low height partitions the work measurement for costing shall be only of the plain visible surface, no extra cost for extrusions or extra frame work required as per drawing will be made. The work done above ceiling, below floor finish level or not directly visible shall not be measured. 1 WALL PANELING (1.0mm Th. Laminate) ON EXISTING PLY PANELING Providing and fixing with approved 1.0mm Th. Laminate on existing 9mm thk.ply paneling. Wooden molding, lipping etc. shall be provided wherever required as per drawing and deco painted in desired shade. The paneling shall have skirting and intermediate bands finished with metallic laminate of desired shade and design. The work shall also include the cost of making cut-outs for the electrical switches, lights, switch boxes etc. and provision for laying conduit 34.81 SO.M for electrical/telephone/Data cabling etc. Also 3" X 1/2" teak wood section shall be provided on exposed surface. Payments shall be made only for exposed surfaces and actual measurement at site. No payment shall be made for panelling behind furniture such as tables, side credenzas, storage,etc. Makes :-Laminate: Aica, Greenlam, Marino, Formica EXISTING FULL HEIGHT PARTITIONS WITHOUT MICA & GLASS 2 3.00 SQ.M (a) providing and fixing with approved 1.0mm Th. Laminate of desired shade and design on existing wooden full height partition. Wooden molding, lipping etc. as directed by Bank architect shall be provided wherever required. The partition shall have skirting and intermediate bands finshied with metallic laminate of desired shade and design. (b) The full height partition shall be WITH 8mm clear float glass with etching fixed as per drawing with 75mm x 12mm Teak wood jamb/chaowkhat around glass opening and 12mm x 12mm teak wood beading for fixing of glass on both sides. As per the direction of Engineer-incharge and design. (c) The work to include providing and fixing of partly glazed wooden door shutters using 35mm readymade ISI flush door shutter with 1.0mm thick laminate (Aica / Greenlam / Century) of desired shade and design as per drawing with teak wood frame of 75mm x 40mm. The door shall have 6mm thick teak wood lipping all around the edges. The door shall have vision panels with 8mm thick clear float glass with etching fixed with double 14mmx25mm thick teak wood moulding as per design. The exposed surface of wood shall be deco painted in desired shade. The door shall be complete in all respect with hardware handles, godrej 6-lever lock/night latch lock, door stoppers, 8" tower bolts, hinges, Door closer etc all in brass. (Hettich /Godrej/Dorma/Ozone) Makes :-Laminate : Aica, Greenlam, Marino, Formica EXISTING LOW HEIGHT PARTITIONS WITHOUT MICA & GLASS 3.93 SO.M (a) Providing and fixing with approved 1.0mm Th. Laminate of desired shade and design on existing wooden low height partition . Wooden molding, lipping etc. as directed by Bank architect shall be provided wherever required. The partition shall have skirting and intermediate bands finished with metallic laminate of desired shade and design. (b) The low height partition shall be provided with 12 mm thick glass with etching as per design fixed with stainless steel wall cladding profile (WCP) of Hettich /Godrej/Dorma/Ozone make at bottom and sides with top surface and other side free. All the edges of the 12mm glass shall be duly grinded/bevelled and polished. Makes :-Laminate : Aica, Greenlam, Marino, Formica



4	EXISTING OFFICER'S TABLES WITHOUT SIDE CREDENZA				
4	EAISTING OFFICER'S TABLES WITHOUT SIDE CREDENZA				
	(a) Providing and fixing with 1mm thick Laminate of desired shade and design on outer visible				
	surfaces; single color on horizontal surface & two color on vertical surfaces on existing officer				
	table. The front of the table top shall be projected and curved as per drawing. Provision for 3"				
	dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables				
	at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping				
	will be provided on all the edges of the table, including bottom touching the floor and the drawers.				
	diawers.				
	The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 19mm ply				
	fixed with sliding telescopic channels of Hettich /Godrej/Hettich make. The work shall also				
	include provision of foot rest made with wooden member of section 3" x 5" along the leg				
	space.				
	(b) Existing storage cabinet shall have three lockable drawer running on side mounting drawer				
	slides (channels) & one cupboard with shutter beneath the drawer, made of 19mm thick				
	commercial block board with 1mm thick laminate of desired shade and design on front face,				
	handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood &				
	front of 19mm thick block board.				
	All other surfaces i.e. inside / leg space of table, inside of drawer / cupboard shall be provided				
	with 0.8mm thick laminate of desired shade and design, and wood lipping / beading shall be			1	
	PU polished with matching pigment/deco painted in desired colour. The table shall have a CPU ledge made of 19mm thick block board on one side, complete as per drawing.			1	
	cr o reage made of 17 min tinck block board on one side, complete as per drawing.				
	Makes :-				
	Commercial ply: Century, Greenply, Duro, Amulya				
	Laminate : Merino / Century / Greenlam New Mica, Amulya				
	Telescopic Channels : Hettich / Haffele / Godrej				
	Drawer locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
	$OFFICER\ (1.52X0.76X0.76\ /1.52X0.60X0.76)\ without\ mica\ , storage\ shutters\ and\ foot\ rest$	2.00	no.		
1	OFFICER (1.52X0.76X0.76 /1.52X0.60X0.76) storage shutters and foot rest	2.00	no.		
	OFFICER (1.52X0.76X0.76 /1.52X0.60X0.76) storage shutters and foot rest	2.00	no.		
5		2.00	no.		
5	OFFICER (1.52X0.76X0.76 /1.52X0.60X0.76) storage shutters and foot rest  BRANCH MANAGER TABLE WITH SIDE CREDENZA	2.00	no.		
5	BRANCH MANAGER TABLE WITH SIDE CREDENZA	2.00	no.		
5	BRANCH MANAGER TABLE WITH SIDE CREDENZA  (a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place,	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design and gloss on front face. The credenza will have drawer compartment 16" wide outer to outer,	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design and gloss on front face. The credenza will have drawer compartment 16" wide outer to outer, containing three drawers vertically running on side mounting drawer slides(channels). The	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design and gloss on front face. The credenza will have drawer compartment 16" wide outer to outer, containing three drawers vertically running on side mounting drawer slides(channels). The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood &	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design and gloss on front face. The credenza will have drawer compartment 16" wide outer to outer, containing three drawers vertically running on side mounting drawer slides(channels). The	2.00	no.		
5	(a) Providing and fixing on existing Branch manager table with 10 mm plain glass on top and with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.  The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.  (b) Existing storage cabinet shall with three lockable drawer running on side mounting drawer slides (channels) & one cupboard with shutter beneath the drawer, made of 18mm thick commercial block board with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick block board.  c) Existing side credenza with 1.0 mm thick laminate as per selection of Architect or Engineer in charge on horizontal surface & one vertical visible side only, polish of desired shade, design and gloss on front face. The credenza will have drawer compartment 16" wide outer to outer, containing three drawers vertically running on side mounting drawer slides(channels). The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 19mm thick block board. The remaining part of the credenza will have cupboard with	2.00	no.		



	All other confesses is inside / les areas of table inside of durance / comboand shall be recavided				
	All other surfaces i.e. inside / leg space of table, inside of drawer / cupboard shall be provided with 0.8mm thick laminate of desired shade/design and gloss, and wood lipping / beading				
	shall be PU polished with matching pigment/deco painted in desired colour. The table shall				
	have a CPU ledge made of 18mm thick block board on one side, complete as per drawing.				
	and a cr c reage made or round after cross court on one stac, complete as per drawing.				
	Makes :-				
	Commercial ply: Green ply ( Eco- Tech ) / Duro / Century/Amulya				
	Laminate : Merino / Century / Greenlam New Mica / Amulya				
	Telescopic Channels : Hettich/ Haffele / Godrej				
	Drawer locks : Hettich/ Haffele / Godrej				
	Auto lock : Hettich/ Haffele / Godrej				
	·				
	BM table (6'-0" x 3'-0" x 2'-6") Side Rack (3'-6" X 1'-6" X 2'-6")	1.00	NOS		
		1.00	1105		
6	EXISTING SWO COUNTERS WITHOUT MICA				
<u> </u>	(a) Providing and fixing with 1mm thick laminate of desired shade and design on outer visible				
	surfaces; single color on horizontal surface & two colors on vertical surfaces on exising Swo				
	counters . Provision for 3" dia. Round /3" square stainless steel of grade 304 cable manager				
	for computer / electrical cables at appropriate place, will be made in the top surface of the				
	counter. Teak wood lipping will be provided on all the remaining edges of the counter,				
	including bottom touching the floor and the drawers. The counter shall have wooden	5.00	NOS		
	keyboard rest of size 600mmx 270mm fixed on sliding telescopic channels of Hettich/Godrej.	5.00	NOS		
	The work shall also include provision of foot rest made with wooden member of section 3" x				
	5" along the leg space.				
-	(h) The counters shall have three self-legishin discuss a self-legishing discussion and the second of				
	(b) The counters shall have three self lockable drawers running on side mounting drawer				
	slides (channels) with 1mm thick laminate of desired shade and design on front face & 3 nos.				
	self locking drawer locks be provided on one side of the counter as per layout on existing drawers. All other surfaces i.e. inside / legsapce of table, inside of drawer/Cupboard shall				
	be provided with 0.8mm thick laminate of desired shade and design, and wood lipping /				
	beading shall be PU polished with matching pigment/deco painted in desired colour. The				
	drawers shall have partitions for keeping currency notes as per drawing, complete in all				
	respects including the required stainless steel hardware like handles, hinges etc.				
	respects including the required stanless steer hardware like handles, filliges etc.				
	Makes :-				
	Commercial ply: Century, Greenply, Duro/Amulya				
	Laminate : Merino / Century / Greenlam New Mica/Amulya				
	Telescopic Channels : Hettich / Haffele / Godrej				
	Drawer locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
	, ,				
7	EXISTING SIDE CREDENZA WITHOUT MICA				
	Providing and fixing with 1mm thick laminate on top horizontal surface & one vertical visible				
	side only, with teak wood lipping on all edges including bottom touching floor on existing side				
	credenza. The credenza will have drawer compartment 16" wide outer to outer, containing				
	three drawers vertically running on side mounting drawer slides(channels). The remaining part	3.00	No.		
	of the credenza will have cupboard with Overlapped shutters and one shelf. All the internal	2.00	110.		
	surfaces shall be finished with 0.8mm thick mica of desired shade and design and the exposed				
	wood shall be deco painted/malamine polished in desired shade.				
	Makes :				
	Makes:-				
<b>-</b>	Commercial ply: Century, Greenply, Duro/Amulya				
-	Laminate: Merino / Century / Greenlam New Mica/Amulya				
<u> </u>	Telescopic Channels : Hettich / Haffele / Godrej				
	Drawer locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
8	EXISTING LOW HEIGHT STORAGE CABINETS/BACK STORAGE WIHOUT				
	MICA				
	(a) Providing and fixing with 1mm laminate of approved shade on vertical and horizontal				
	visible surfaces on existing storage cabinets. All existing shutter expose edges to be Polished				
	with edge bending tape of desired shade. The inner surface shall be provided with 0.8mm thick	13.64	RM		
	laminate of desired shade and design. The cabinet shall be complete with handles, knobs, locks				
	and magnet catchers etc. to the satisfaction of the Architect/Engineer.				
1	ı		I	I .	1
	Makes :-				



	Commercial ply: Century, Greenply, Duro, Amulya				
	Laminate : Merino / Century / Greenlam New Mica/Amulya				
	Telescopic Channels : Hettich / Haffele / Godrej				
	Drawer locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
	Auto lock : Hetticii / Haifele / Gourej				
_					
9	EXISTING GYPSUM BOARD FALSE CEILING WITH STEPS:				
		88.51	SQ.M		
	Providing and fixing masking/jointing tape on joints including 2-3 coats of oil bound				
	distemper, over a coat of primer. The work should be complete in all aspects of Architect /				
	Engineer in charge				
	Makes :-				
	Gypsum Board :- Saint Gobain / Gypcore/ USG Knauff				
	Ceiling Channel, Angle Screws Etc. :- Saint Gobain / USG Knauff				
	7 0				
10	GRID FALSE CEILING:				
10	GRID FALSE CEILING.	(5.42	COM		
	Desidies and Geissen in the second of the 15 - 42 - 2000 are and 4 (00 are and 4)	65.42	SQ.M		
	Providing and fixing main runner of size 15 x 42 x 3000 mm spaced at 600 mm centers				
	securely fixed to the structural soffit by approved hangers at 1200 min maximum centers				
	hangers (BUTTERFYLY CUP) to be fixed by approved roof plug, level adjusters, screws etc				
	the last hanger at the end of each main runner should not be greater than 450mm from the				
	adjacent wall, 600mm x 600mm modules to be formed by fitting 600mm long flush fitting				
	cross tees of size 15 x 42 x 600mm centrally between the main runners Penmeter wall angle of				
	size $19 \times 19 \times 3000$ mm secured to walls at 450mm maximum centers finally dune supreme ml edge rh $-99\%$ 15 mm thick (nrc-0.50,light reffectance $> 85\%$ . Can- 34 db, k value = 0.052 to				
	0.057 w/m k) micro look edge has to be laid on the 600 mm x 600 mm module (the same				
	ceiling shall be fixed by using full size files only & shall be fixed to the gypsum false ceiling.				
	N 1				
	Makes:-				
	Grid Tile :- Armstrong / Knauff				
	Ceiling Channel, Angle Screws Etc. :- Saint Gobain / USG Knauff				
11(a)	EXISTING WOODEN CEILING WITHOUT TEAK PLY AND WIHOUT POLISH				
11(4)	End in to the object to the ob				
	Providing and applying 4mm thk.teak ply PU polishing and polyeurethene coating etc on				
	existing ceiling over 12mm commercial ply. The payment area will be the visible area only The	5.94	SQ.M		
	work should be complete as per instructions of Architect or Engineer in charge.	3.74	5Q.M		
	work should be complete as per instructions of Architect of Engineer in charge.				
	Makes:-				
	Commercial ply: Century, Greenply, Duro, Amulya				
	Teak ply : Merino / Century / Greenlam New Mica/Amulya				
	Ceiling Channel, Angle Screws Etc. :- Saint Gobain / USG Knauff				
b	WOODEN CEILING (TEAK PLY) - WITHOUT POLISH		<del> </del>	+	
D	WOODEN CEILING (TEAK FLT) - WITHOUT POLISH		-		
	Providing and applying PU polishing and polyeurethene coating etc on existing ceiling over				
	12mm commercial ply. The payment area will be the visible area only The work should be	13.19	SQ.M		
	complete as per instructions of Architect or Engineer in charge.		~ <b>Q</b>		
12	EXISTING WOODEN BOXING FOR ELECTRICAL PANEL WITHOUT MICA				
14	EARSTING WOODEN BOAING FOR ELECTRICAL PANEL WITHOUT WICA				
	Providing & fixing on existing electrical panel box with shutter & 1.0 mm thick laminate . All				
	accessories like ball catches, ss handle, Fixing MS powder cotted perforeted jali shall be				
	provided in shutter top & bottom etc. All internal frames 50mm x 25mm x 1.6mm thick section	67.25	SQ.FT		
	at maximum 2'-0" c/c. Complete as directed depth of cup board 1'-6". Measurement shall be	07.23	5Q.F I		
	based on area of front elevation of cupboard. The rate to include all materials, labour, transport,				
	taxes, etc complete as directed. As per approved hardwere list.				
	tailes, etc complete as affected. Its per approved hardwere his		1	1	1
	antes, the complete as different his per approved made note his				
	Makes:-				
	Makes :-				
	Makes :- Commercial ply: Century, Greenply, Duro, Amulya				
13	Makes :- Commercial ply: Century, Greenply, Duro, Amulya				



	Providing and Fixing of pantry storage cabinet depth 600mm with shutters made in 19 mm thick com. block board and 6mm thick com ply for back side to be fixed on the wall, with 19mm thick com. block board shelves inside placed horizontally with self closing bright finished CP hinges,inside 0.8 mm thk laminate finish and shutters finished with 1 mm thick laminate of approved color and shade .The item includes providing 150mm SS finished handles on front for shutters,including necessary hardware etc. all complete as per drawing and to the instruction of Engineer in charge .	2.75	SQ.M		
	Makes :-				
	Commercial ply: Century, Greenply, Duro, Amulya				
	Laminate : Merino / Century / Greenlam New Mica/Amulya				
	Telescopic Channels : Hettich / Haffele / Godrej				
	Locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
14	OVER HEAD STORAGE CABINET FOR PANTRY				
	Providing and Fixing of <b>Pantry over head storage</b> cabinet depth 400mm, height 600mm with shutters made in 19 mm thick commercial block board and 6mm thick com ply for back side to be fixed on the wall, with 19mm thick commercial block board shelves inside placed horizontally and vertically with piano hinges. All inside surfaces to be 0.8 mm thk laminate and outer faces of shutters and sides (excluding outer top and bottom faces which are to be enamel painted) to be finished with 1 mm thick laminate of approved color and shade. The item includes providing 150mm brass handles on front for shutters, magnetic catchers, including necessary hardware etc. all complete as per drawing and as per instruction of Engineer in charge.	1.75	SQ.M		
	Makes :-				
	Commercial ply: Century, Greenply, Duro, Amulya				
	Laminate : Merino / Century / Greenlam New Mica/Amulya				
	Telescopic Channels : Hettich / Haffele / Godrej				
	Locks : Hettich / Haffele / Godrej				
	Auto lock : Hettich / Haffele / Godrej				
15	EXISTING RECTANGULAR WRITING DESK WITH STORAGE WITH CUSTOMER AND COMPLAINT BOX AS PER DRGS.				
	Providing & fixing with 1 mm thick laminate on all sides including inside divisions on existing rectangular writing desk . 12mm thick toughen glass Shelf shall be fixed of desk with bevelled and polished edges making different divisions by 12mm thick toughen glass for slips or forms as per detail drawing directed complete. The rate to include all materials, labour, transport, taxes, etc complete as directed. (Size: 4'-0" X 1'-0" X 3'-6"ht.)	1.00	NO.		
	Makes :-				
	Commercial ply: Century, Greenply, Duro, Amulya				
	Laminate : Merino / Century / Greenlam New Mica/Amulya				
	Telescopic Channels: Hettich / Haffele / Godrej			1	
	Locks : Hettich / Haffele / Godrej			1	
	Auto lock : Hettich / Haffele / Godrej			1	
16	FIRE PROOF DOOR FRAME (4'-0" X 7'-0")				
	Providing and fixing fire resistant door frame of section 143 x 57 mm having built in rebate made out of 16 SWG G.I. Sheet (zinc coating not less than 120 gm/sqm) duly filled with vermuculite based concrete mix, suitable for mounting 60 minutes fire rated door shutters. The frame is fitted with intumuscent fire seal strip of size 10x4 mm (minimum) alround the frame and fixing with dash fastener of approved size and make, including applying a coat of approved brand fire resistant primer etc. complete as per direction of Engineer-in-charge (including Dash fastener).	1.00	NO.		
b	FIRE PROOF SHUTTER			1	
	Providing and fixing 50 mm thick glazed fire resistant door shutters conforming to IS:3614 (Part-II), tested and certified as per laboratory approved by Engineer-in-charge, with suitable mounting on door frame, consisting of vertical styles, lock rail, top rail 100 mm wide, bottom rail 200 mm wide, made out of 16 SWG G.I. sheet (zinc coating not less than 120 gm/ m2) duly filled FR insulation material and fixing with necessary stainless steel ball bearing hinges of approved make, including applying a coat of approved fire resistant primer etc. all complete as per direction of Engineer-in- charge (paneling to be paid for separately)				
c	FIRE PROOF GLASS PANEL				



Providing and fixing glazing in fire resistant door shutters, fixed panels, ventilators and partitions etc., with G.I. beading of appropriate size, made out of 20 SWG G.I. Sheet (zinc coating not less than 120 gm/ m2), fire resistant sealant, including applying a coat of approved fire resistant primer on G.I. beading etc., complete all as per direction of Engineer-in-charge.		
With clear fire resistant glass panes 6 mm thick of approved brand, having minimum 60 minutes fire resistance		
Makes:-		
Fire Door :- SBG/GMP/Kutty's Doors		
Total Value of Works		
NOTE: GST SHALL BE EXTRA		

