

BOQ FOR INTERIOR & FURNITURE WORK AT ALTERNATIVE PREMISES

COMMERCIAL BRANCH G S ROAD GUWAHATI

Sl.No	Description of items	Unit	Qty	Rate(Rs.)	Amount(Rs.)
1	<p>SWO COUNTER: Supply and installing new SWO Counters of overall size 1500 mm X 750 mm X 750 mm, including cost of side credenza (1200mm x 450 mm x 750 mm) made up of 19 mm thick Block board of approved brand all around and finished with laminate of not less than 1 mm thick of approve colour, brand and shade. The cost to include three drawers of 375 mm wide made up of 6mm/12mm ply of approved brand on right hand side of the table on telescopic slider with partitions for keeping of notes of different denominations, a keyboard tray 250 mm wide, CPU stand, foot rest as design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to be finished with laminate. All inner surface to be finished with 0.8mm laminate finish of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved make. Locks to be of single control type. Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy, with curvature on front with flexi ply with 1mm laminate tfinish. Counter & Credenza top to be provided with 8mm thick glass duly finished on edges and necessary cut to accommodate wires, edges to be m/c polished, with ms powder coated wire manager, complete as directed by EIC and placement as per layout given.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Apple/White/Cotton/White/Orange/Red</p>	Each	5		
2	<p>Providing & fixing counter Front 12 mm thick float glass with polished edges, fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Rate shall include fixing of frost film as per design & directed, cost of studs, making cut-outs for transaction and voice hole. Make: Saintgobin/ Modiguard or equivalent.</p>	SQM	3.24		
3	<p>Providing & Fixing 12 mm thick float glass of size 320mm (width) x 1100mm (height) & tapering towards bottom as per the design and shape as shown in Bank's new uniform colour, layout & elevation policy, fixed with silicon and T.W beading support on wooden partition as directed, on either sides of SWO as per design. Rate shall include etching of glass as directed by bank. All edges of glass shall be duly bevelled & polished as directed complete. Make: Saintgobin/ Modiguard or equivalent.</p>	SQM	2.1		

4	<p>Supply and installing table of size-2100 mm x 900 mm x 750 mm including cost of side credenza (1200mm x 450mm x 750 mm) for DGM made up of 19mm thick Block board all around, finished with not less than 3 mm thick veneer of colour, shade & brand as approved with melamine / PU finish. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on right hand side on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to be finished with approved veneer 3mm thick with melamine / PU finish. All inner surface to be finished with 0.8mm laminate of approved shade. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in veneer finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Veneer Make: Greenlam/Century/Merino/Archid or equivalent.</p>	Each	1		
5	<p>Supply and installing table of size- 1800 mm x 750 mm x 750 mm including cost of side credenza (1200mm x 600mm x 750 mm) for AGM/RM/CM made up of 19mm thick Block board all around, finished with not less than 1 mm thick laminate of colour, shade & brand as approved. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on right hand side on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to be finished with approved laminate. All inner surface to be finished with 0.8mm laminate of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.</p>	Each	6		

6	<p>Supplying and installing Tables for Grahak Mitra and cross selling staff table of Overall size - 1680 mm X 600 mm x 750 mm made up of 19mm thick block board of approved brand all around and finished with not less than 1 mm thick laminate colour, brand and shade as approved by the Bank. The table cost to include (pedestal) three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide with CPU stand and foot rest as per design and direction by Bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have to match the desk and finished with laminate . All inner surface to be finished with 0.8mm laminate of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type.Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.</p>	Each	1		
7	<p>Supplying and installing Tables FOR OFFICERS of Overall size - 1500 mm X 750mm x 750 mm including cost of side credenza (1230 mm x 450 mm x 750 mm) made up of 19mm thick block board of approved brand all around and finished with not less than 1 mm thick laminate colour, brand and shade as approved by the Bank. The table cost to include (pedestal) three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide with CPU stand and foot rest as per design and direction by Bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to be finished with approved laminate. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type.Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy.</p>	Each	25		
8	<p>LINEAR / RUNNING WORK STATION: Providing and fixing linear / running Work Station having a size of 1500mm X 750mm X750mm ht. in 19 mm thk. Exterior Grade Block Board of approved make for table top and side supports. The Front apron in 12mm.thk. bwp ply with approved colour Laminate & on fixed Raised panel in 12mm. Thk. Finished In approved colour Laminate for all exposed surface, fixed with S.S. Studs & the top and sides of the counter to be finished on both sides with 1 mm thk. Laminate of approved make and shade / design. A Powder coated Wire manager ,Key Board Drawer size 300mm x 500mm x 50mm deep made out of 12mm. thk. Ply ,Wooden Beading Patty four side in Laminate finish run on with Heavy duty sliding Chanel , A drawer unit of size 400mm X500mm X725mm in 19 mm bwp ply with three drawers as per the drawing etc complete.(Low height partitions abutting the counters will be paid separately &also the Counter Length to be checked during execution as per plan / Site Condition)..Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.</p>	RM	3.6		

9	Providing and fixing floor mounted writing desk of size 1200mm x 300mm x 900mm(H) made of 19 mm/ 12 mm ply finish with not less than 1 mm thick laminate and with 12 mm thick float glass on top and voucher pigeon holes as per design & direction of bank, with laminated boards support.Board. Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or	Each	1		
10	Low ht storage unit: Providing and fixing storage units of size 450 mm x 750 mm, made up of 19 mm thick block board of approved brand on top & vertical support and finished with not less than 1 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to be finished with 0.8mm thick laminate. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, ,locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	RM	62.73		
11	Full Height storage unit: Providing and fixing storage units(height cieling height i.e 2.4 (approx) made up of 19 mm thick block board of approved brand on top & vertical support and finished with not less than 1mm thick laminate of approved brand. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have three intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to be finished with 0.8mm thick laminate. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, ,locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	sqm	36		
12	Fabricating and fixing column/wall paneling with 8 mm thick ply finished with not less than 1 mm thick laminate and 3mm veneer of approved shade & brand over framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Panelling framework to be secured to wall surface / column surface. Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate/Veneer Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.				
a)	For Hall area,customers space,office space etc. (With 1mm thick LAMINATE FINISH)	SQM	335		
b)	For DGM CABIN and sitting lobby near conference room(3mm VENEER with Melamine/PU Finish)	SQM	30		
13	Fabricating and fixing full height solid partition, made of 8 mm ply approved brand both side and to be finished with not less than 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) aluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. All exposed edge shall be covered with wood bidding/lipping of required size with polishing complete in all respect. Payment will be made for the area upto false ceiling only. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	97.88		

14	<p>Proving and fixing 12mm tinted toughened glass frameless partition with door of brand saintgobain/Asahi brand .The item is including hardware items,ss304,silicon, caring including installation and fitting charge. The rate shall be inclusive of fixing film over glass. The item shall be inclusive of best quality SS floor springs, handles and locks complete</p>	SQM	171.73		
15	<p>Providing and fixing low height semi glazed wooden partitions made of 8 mm ply of approved brand in both side and to be finished with not less than 1 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) framework of approved aluminium brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Top portion from 900 mm to 1500 mm height shall have 12 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick wood moulding duly polished as per design and direction by bank. All exposed edge shall be covered with teakwood lipping with polishing complete in all respect. Rate shall include making provision for fixing of counter top 12 mm glass on its edges with necessary fixing arrangment as directed. Rate shall include etching of glass as required by bank.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent. Glass make : Asahi /Saint gobain</p>	SQM	47.77		
16	<p>Providing and fixing Semi glazed doors shutter made up of 38 mm thick block board of approved brand and quality, finshed both side with not less than 1 mm thick laminate of approved brand, colour and shade. Middle portion at 900 mm to 2100 mm height shall have 8 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with wood lipping with polishing complete all respect. Rate shall include etching of glass as required by bank.</p> <p>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent. Glass make : Asahi /Saint gobain</p>	SQM	6.87		
17	<p>Providing & fixing in position Aluminium Composite Panel (ACP) / Shutter boxing Panelling with framing in 600 mm C/C both ways. Minimum 3 mm thick ACP to be fixed over the freamework with 3M or equivalent adhesive and mirror screw in 600 width panels or distributed equally. Joints to be finished with Silicon based sealant. The shade /colour will be as per the direction of bank.</p> <p>Make: Alubond, Eurobond, Fujibond, Alcobond or equivalent ISO certified or approved brands to be used.</p>	SQM	8.64		
18	<p>Providing & fixing in place 100 mm. Vertical blinds with scotch guard of approved make, quality and colour shade & pattern. Rate shall include necessary fittings, scotch guard treatment on both sides etc. complete. The overlaps should be uniform & adequate. Brand :Vista fashion, IKEA,Hunter douglass</p>	SQM	160		
19	<p>Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure doors</p>	Each	5		
20	<p>MAIN ENTRANCE DOOR AND DGM DOOR :ENTRANCE DOOR DOUBLE SHUTTER OF SIZE 5' X 7'-0"AND DGM DOOR SIZE 3'-6"X 7'-0" : Providing & fixing main door made up of 12 mm thk. Clear toughen glass on Floor Spring (Weight Capacity upto 100 Kg) shall be fixed in.Ozon / Enox make patch fitting with necessary hardware like floor spring, 18" S.S. finished decorative handle pair,& locking arrangment. Edge polish for all exposed sides of glass. Complete as per design .The door shall be finished with either etching or film over glass. Make: Saintgobin/ Modiguard or equivalent.</p>	SQM	3.6		

21	Full height Partitions fully glazed with Glass:Providing & fixing fully glazed partitions with 12mm toughened clear float glass of brand Saint Gobain/ Asahi India glass Ltd. (ENTRANCE)Make: Saintgobin/ Modiguard or equivalent.	SQM	5.5		
22	SOFT BOARD / NOTICE BOARD: Providing and fixing Soft Board panelling (3'-0"X4'-0") made out of 12mm thick Soft Board covered with approved colour felt/cloth (Rate Rs. 350/-) on 8 mm.Thk. bwp Grade ply backing	NO	3		
23	WALL PUTTY Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	SQM	662		
24	PAINTING WORK : Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour. Two coats	SQM	662		
25	ENAMEL PAINT IN EXISTING ROLLING SHUTTER, COLLAPSABLE GATE,GRILLS & OTHER M.S WORKS: Providing & applying 1st quality oil paint of approved make, quality & shade. The rate shall include scrapping, levelling & preparing the surface with primer quote.	SQM	35		
26	Gypsum False Ceiling :Plain Gypsum Ceiling:- Supply and installation of 12.5mm thick plain gypsum plaster board Suspended by using C System which includes Main channel at every 1200mm . Frame work shall consists of GI perimeter channels of size 0.45mm thick (having one flange of 20mm and another flange of 30mm) fixed along with perimeter of the gypsum or walls with the help of nylon sleeves and screws at 600mm c/c. Then suspend GI main channels of size 0.45 mm (0.9mm thick with 2 flanges of 15mm each) from the soffit at 1200mm c/c by using soffit angle of size 25mm x 10mm x 0.45mm thick fixed to true ceiling by using suitable fasteners. Cross channels of size 0.45mm thickness having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the main channel with the help of connecting clips and in a direction perpendicular to the main channel at 300mm c/c. The Gypsum board will be painted as per selected colour and shade.	SQM	565		
27	False Ceiling (Armstrong): Providing & fixing in position false ceiling in Armstrong 600 x 600 mm x 15/18 mm Dune Supreme RH 99 Prima tile with Tegular edge framework as specified by Armstrong Co. with suspenders wherever required. Making necessary framework for A.C. ducting, if any, and necessary cutouts for diffusers and light fittings, taping and finishing to proper line & level, including making grooves and trap doors for A.C unit in 18mm thick M.R. Grade Plywood with Stainless Steel hinges & locks with moulding 1" x 1" for edges including finishing with White Plastic Emulsion Paint etc. complete in all respects. (Note:- Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, mouldings etc.)	SQM	241		
28	Providing and fixing in position Vox/ Alwud infra top (High Pressure Laminate/PVC-U)Panel ceiling installed with GI Framework (1) main GI channels 15mm x 450mm , fixed with anchor bolts @1000mm centre/centre bothways. (2) Intermediate GI channels 15mm x 80mm @450 mm C/C and wall channels 30mm x 40mm fixed to the brick walls or RCC beam. GI channels complete with all accessories with combination of Oak and Oak Winchester shade PVC interlocking panels or as approved by the bank.	SQM	73.5		

29	HDPC STRIP PANELS on ceiling & wall panel system of Bollard/Armstrong/Merino Miraki hdpc panels MRC6056/6057 Colour Fusion Maple / mahogany of size 192mm x 2440mm x 15mm ,NRC 0.6/0.85 OF LAMINATE SURFACE FINISH .	SQM	48		
	SOFA:				
30	Providing and placing in position L- shaped corner fabric sofa -right aligned 2 seater+left aligned 2 seater+ corner by urban ladder,boss cabin etc..	NO	2		
31	Providing and placing in position 3- seater fabric sofa in the shade of cobalt blue	NO	4		
32	Providing and placing in position 1 seater fabric sofa in the shade of cobalt blue of n	NO	3		
33	Providing and placing in position 3+1+1 seater leather sofa in DGM'S Room	NO	1		
34	Centre Table : Providing and fixing in position Centre table fabricated our 38mm x 38mm teak wood frame as per design . Size of table 600mm x 600mm x 350mm. The table shall be provided with 6mm thick glass top and laminated 12mm thick ply base (Magazine rack) at lower level.	NO	5		
35	Side Table size 450 x 450x 350	EACH			
36	Providing and fixing Bank's Lighting Logo on blank wall as display with lighting facility.	NO	4		
37	Planter Box: Made out of 18mm BWP ply finished with 1.5mm thk laminate of approved shade. All the groove designs and the skirting designs have to be strictly followed from the drawings attached.	NO	12		
38	Providing and fixing wall paper for canteen wall as per approved design and shade by the Bank and Architect.	SQM	30.16		
	Pantry and Kitchen storage unit				
39	Overhead Storage unit : Providing and fixing storage overhead made of 19mm thick exterior grade Phenol Formaldehyde bonded block board including providing 1.5mm thick laminated sheet in matt finished of approved make and shade including first class timber frame work. All exposed edges of the block are to be covered with Teak wood lipping as per design. Rate to includ charges for brass hardware fittings as well as fixtures complete as per drawing. (Approx. size 300 mm depth and 750mm height).Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	7.42		
40	Cupboard: Providing and placing in position cupboard for pantry and Kitchen below platform fabricated out of sal wood frame size 50 x 75 mm with shutters fabricated out of waterproof ply 19mm thick and 1mm laminate finish complete with hardware and painting. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	9.52		
	DISPLAY UNIT FOR CONFERENCE				
41	Providing and placing in position display units fabricated out of BWR 19mm block board/ 12mm thick BWR ply and finished with laminated / veneer as directed complete with 12mm glass shelves completed with varnishing (Approx Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.size 2000 x 2400 x 600), partly finished with veneer/chemical etching/ glass mosaic (logo shall be provided as per design)	SQM	20		
	CONFERENCE ROOM ITEMS				
42	CONFERENCE TABLE				

	19 SEATER CONFERENCE TABLE Providing and placing in position U - SHAPED conference table OF SIZE 2100MMX6300 fabricated out of the following--	no	1		
	Work Surface. Supplying and placing in position of table as per photograph/drawing. The Table top are made out of 36mm thk plain MDF Board with 12MM white Corian solid surface finish. The table top with Provision of flip top box (3 to 6 nos) for wire management and raceway under the table top for wires flow.				
	Understructure: The understructure shall be supported with side panel of 32mm thk plain MDF Board with veneer finish PU polish and modesty panel are made out of 18mm thk plain MDF board with Veneer finish PU matt polish. All exposed edges shall be provided with veneer finish and polishing.				
	Modesty Panel: Made of 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade conforming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping.				
	Wire Management: An array of panels made of 0.8mm and 1.2 mm CRCA MS IS:513, epoxy polyester powder coated (DFT 40-60 microns) is used for flow of wires and cables. Cutout for Standard Anchor Roma 4 module is provided for electrical fittings in Straight two seater and single seater modules below access flap per seat.				
	Product should be Greenguard (UL), Indoor Advantage Gold, Griha & Svagriha, Greenpro certified and BIFMA Compliant.				
	Size of each Module: 700 (W) X 600 (D) X 750 (H) (9 Seater + 9 Seater + 1 Seater size 900(W)x700mm (D)x750mm(H)MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Veneer Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.				
43	Wall panelling for conference				
	Supply and installation of acoustics fabric pasted Heradesign Fine of size 600x2400x25mm thk by using H-Splines mounted on Strut (having density 12.4 Kg/m ³ , Sound absorption value aw up to 0.90 , Reaction to fire according to EN 13501-1:B-s1,d0 ,Strut is fixed Horizontal to the wall at every 600mm c/c. Perpendicular to Strut position first fix H-Splines, Insert Panel into H-splines section and against wall. The Heradesign Fine panels will be back lined with Glass wool 50 mm 24kg density. Ply /Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	17.28		
44	Veneer on BWP Plywood 1200x2400x12mm (Green / Century) Supply and installation of Plywood 1200x2400x12mm thk (12 mm thick ply having density of 500-600 Kg/m ³ , NRC 0.2, fire rating Class A). 12mm ply is fixed on SoundStrut CC 50 by using fasteners. SoundStrut CC50\ to be fixed horizontally on the wall @ every 600mm c/c. Laminate or Veneer of Approved colour is then fixed on Plywood .	SQM	23		
45	Providing and fixing Knauff Glasswool / Armstrong Acoustical suspended Ceiling tile of size 600X 600 x15mm thk , (having density 15 mm (c. 4.5 kg/m ²) , NRC upto 0.70, Reaction to fire, : A2-s1, d0 as per EN 13501-1, Sound attenuation: Dn,c,w = 34 dB as per EN 20140-9 (15 mm thickness, according to test certificate) , The suspension is done with all accessories like Soffit cleat, leveling clips & wire rods as per the dwgs.	SQM	25.56		

46	STATUE ALCOVE :Providing and placing in position statue alcove fabricated out of 19 mm BWP Block Board size1650MM X600MM X2400MM. Item to be finished externally with 3.5 mm veneer finish with Matt PU coating. Alcove back to be lined with glossy finished glazed tile of approved colour. The Base of Alcove to be provided with Granite Slab of 25 mm Thickness with nosing finish as per Drawing.Lower portion of unit shall be provided with wooden planter. Inner portion lined with G.I. sheeting . External finish of Planter shall be of Veneer of PU MATT finish.	SQM	4		
47	Book shelf Providing and fixingbook shelf unit of size 1800mm x 600mmx 2400mm made up of 19 mm thick block board of approved brand on top & vertical support and finished with not less than 1mm mm thick laminate of approved brand. The book shelf unit shall have openable shutters made up of 19mm thick plywood and 5mm glass shutter with teak wood beading and lipping as per drg and desig by the Architect. and finished in 1 mm thick laminate of approved shade. The storage units shall have six intermediate horizontal and three vertical shelves made in 12 mm thick plywood. All exposed edges to be finished with 0.8mm thick laminate. All inner surface to be also finished with 0.8mm laminate of approved shade. The works to include all hardwares such as: castors, brass hinges, ball catchers, ,locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	4.5		
48	Providing and fixing composite ceiling and side partition above the statue alcove and grahak mitra table with 19mm BWP ply with 1mm blue coloured approved laminate by the Architect.	SQM	10		
49	window curtain (with curtain rod)				
	a) net fabric	SQM	20		
	b)silk fabric	SQM	20		
50	Providing and placing in position 8 seater meeting table of size 750x2100 mmx750mm made out of 19mm block board with 1mm laminate finish.Ply/Block Board. Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent.	NO	1		
51	Providing & placing in position readymade 4 seater dining table with chairs of size 900 mmx750 mm	NO	6		
52	Providing and fixing in position wall mounted table for canteen made out of 19 mm waterproof ply with laminate finish. MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent	rm	5		
53	Readymade Stool for wall hung table	NO	6		
54	Providing and fixing photo frames of size				
	(a) 300mm x 300mm	NO	12		
	(b) 250mm x 450mm	NO	10		
	(c) 300mm x 600mm	NO	6		
	TOTAL				

RATES ARE EXCLUSIVE OF GST