

BOQ FOR CIVIL WORK AT					
SBI, ANJANGYANG BRANCH					
Sl.No	Description of items	Unit	Qty	Rate(Rs.)	Amount(Rs.)
1	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2 mm and braced with flat iron diagonals 20x5 mm size, with top and bottom rail of T-iron 40x40x6 mm, with 40 mm dia steel pulleys, complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.	SQM	10		
2	Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength conforming to IS: 4454 - part 1 and M.S. top cover of required thickness for rolling shutters including Providing and fixing ball bearing for rolling shutters. Rates shall includes applying priming coat. 80x0.90 mm M.S. laths with 0.90 mm thick top cover	SQM	10		
3	Brick work in Cement mortar 1:4 (1 cement : 4 coarse sand) with 1st class bricks including racking out joints and curing complete as directed in all levels. Full brick wall (225 mm).	M3	6		
4	Brick work in Cement mortar 1:4 (1 cement : 4 coarse sand) with 1st class bricks including racking out joints and curing complete as directed in all levels. Half brick wall (112 mm).	SQM	80		
5	12 mm thick cement plaster in single coat on fair/rough side of brick/concrete walls for interior/exterior plastering in all levels finshed even and smooth including curing complete as directed: In cement mortar 1:4 (1 cement : 4 fine sand)	SQM	200		
6	Reinforced Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40 mm ominal size) in pavements, laid to required lope and camber in panels as required including onsolidation finishing and tamping complete.	CUM	2		
7	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Mild steel and Medium Tensile steel bar of 8 mm dia.	Kg	200		
8	Applying & Finishing walls with 2 or more coats of acrylic emulsion paint of approved colour/shade on surfaces after preparation of base with sand papering, POP/Putty required over a coat of primer ofapproved brand. Inlcuding Putty wherever requierd. Make: Asian paint, Deulux	SQM	250		
9	Applying & Finishing walls with 2 or more coat of enamel paint of required shade on wooden and steel surface. Rate including cost of primer coat. Make: Asian paint, Deulux	SQM	75		
10	Wash basin: Providing and fixing wash basin with CI bracked, 15 mm CP brass pillar top, waste cupling, 32 mm pvc waste pipe of standard pattern including painting of fittings and brackets, cutting and making the walls wherever required. White vitreous China wash basin 550 X 400 mm with 15 mm thick C.P. Brass pillar top complete in all sense. Hindware	Each	3		
11	Water Closet: (European type W.C.) Providing and fixing white vitreous china water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required. W.C. pan with ISI marked white solid plastic seat and lid.	Nos	3		

12	2 way bib cock: Providing and fixing two way bib cock with wall flange complete.	Nos	1		
13	Health Faucet: Providing and fixing of hand shower (Health faucet) with 1 metre long easy flex tube in chrome finish & wall hook complete.	Nos	1		
14	PVC Waste pipe: Providing and fixing waste pipe suitable for wash basin model mentioned in item no 5 above, including P.V.C. waste fittings complete 40 mm dia	Nos	3		
15	Connection pipe: Providing and fixing connection pipe with unions suitable for wash absin and water closet mentioned above.:	Nos	3		
16	Pillar Cock: Providing and fixing of pillar cock for basin complete.	Nos	3		
17	Angular Stop cock: Providing and fixing of angular stop cock with wall flange complete.	Nos	6		
18	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.	Nos	1		
19	Urinal: Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350, including drain pipes, painting of fittings and brackets, cutting and making good the walls and floors etc. wherever required : (make:Cera/Parryware).	Each	1		
20	Providing and fixing UPVC/HPVC pipes complete with fittings and clamps, i/c cutting and making good the walls etc. Internal work - Exposed on wall 40 MM dia/ 25 mm dia/ 15 mm dia	RM	30		
21	Providing and fixing PVC (6kg) darinage pipes complete with fittings and clamps, bends etc complete as per direction of engineer in charge. 110 mm dia	RM	25		
22	Ceramic glazed wall tiles : Providing and fixing 300 x 300 mm size 8 mm thick 1st quality ceramic glazed wall tiles conforming to IS: 15622 of approved make, in all colours, shades approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) or 5 to 8 mm thick Balendura / Latticrate adhesive as advised and jointing with matching shade cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete including dismantling of existing tiles if any.. Make: Kajaria / Jhonshon/marbito	SQM	35		
23	Non skid Bathroom floor tiles : Providing and laying Ceramic non skid bathroom floor tiles of size 300 x 300 mm 8 mm thick of approved make and shade, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), or 5 to 8 mm thick Balendura / Latticrate adhesive, as advised including pointing the joints with white cement and matching pigments etc. complete including dismantling of existing tiles if any. Make: Kajaria / Jhonshon/Marbito	SQM	10		
24	Suply and fixing of WPC flush door with WPC Frame for washroom of approved quality and size..	Nos	3		
25	Providing and laying vitrified tiles in floors, in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm	SQM	120		
26	Brick on edge flooring with bricks of class designation 7.5 on a bed of 12 mm cement mortar, including filling the joints with same mortar, with common burnt clay non modular bricks: 1:6 (1 cement : 6 coarse sand)	SQM	5		
27	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	SQM	5		

28	Making of one kitchen slab for cooking area of size 3000 mm x 600 mm x 75mm made of RCC and finixed with tilies.	NOS	1		
29	Supply and fixing of one kitchen sink with all necessary fittings	NOS	1		
30	Construction of ramp of size 900 mm x 2500 mm with all necessary brck and concrete work, fixing of tilies, railing etc all complete.	JOB	1		
31	Demolition of brick wall tiles, pcc floor and removal of debris from site and disposal as per muncipal norms	Job	1		
TOTAL(EXCLUDING GST)					