

STATE BANK OF INDIA

Schedule of Quantity for Interior Furnishing Work at the New Premises of SARB-II, KOZHIKODE

Date:

Sr.No	Description	Qty	Unit	Rate	Amount
1	Low Height Partitions	75.00	Sq M		
	<p>Providing & fixing low height wooden partition finished with both sides laminate and glass:- Height of the partition will be max 1,200mm (Solid portion of 900mm height and top portion with 10mm toughened glass of 300mm height).</p> <p>(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 450 mm bothways (horizontal and vertical) fixed rigidly on floor, wall / column. The end vertical frames shall be extended up to 1,200mm.</p> <p>(ii) Plywood skin:- Providing & fixing 9mm thick MR plywood IS 303 on both sides of the framework and alround vertical posts extended upto 1200 mm height.</p> <p>(iii) Finishing:- With 1.00mm thick laminates of approved quality and shade to be finished over ply as per design & pattern shown in Architectural drawing or as directed by the Engineer.</p> <p>(iv) Glazing:- Providing and fixing 12 mm thick glass with polished edges as partitions and fixing the same with french polish/ 'SS Satin Finish' 'D-clamps' horizontally at maximum 70cm starting & ending at 10cm from inner face of vertical post and on vertical post at 20cm from top, the edges should be smooth complete.</p>				

Sr.No	Description	Qty	Unit	Rate	Amount
	<p>(v) 38x95mm TEAK wood moulding to be provided on top and side edges of partition .complete with melamine matt polishing/ Duco paint including proper base etc.The rate shall include all necessary hardware, making necessary cutouts for electrical conduits / cables & swithboards, AC ducts etc., including necessary support for doors as per drawings/ directed by Engineer..</p> <p>Approved make:-</p> <p>(a) Aluminum extruded sections: Jindal, Hindalco or approved equivalent</p> <p>(v) 38x95mm TEAK wood moulding to be provided on top and side edges of partition .complete with melamine matt polishing/ Duco paint including proper base etc.(b) Plywood:- Greenply, Century, Duro or approved equivalent.</p> <p>(c) Laminte:- Greenlam or equivalent</p> <p>(d) Glass: Saint Gobain, Asahi Float, Modi Guard.</p>				
2	Full Height Partly Solid & Partly Glazed Partition:	32.00	Sq M		
	Providing and fixing in position of double skin partition, partly paneled and partly glazed as per details shown in the drawing.				
	<u>Frame Work Detail:</u> Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm bothways (horizantal and vertical) fixed rigidly on floor, wall / column & ceiling.				
	Lining Work:Providing & fixing 9mm thick MR plywood IS 303 on both sides of the framework. from floor level to 900 mm level and 2100 mm level to 6" above false ceiling level finished with 1 mm laminate of approved color and shade. Between 900 mm and 2100 mm level, 10 mm thick clear float glass with etching fixed with necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick. The glass opening 'jamb' portion finished with laminate.				
	Measurement for the partition area shall be considered from the floor level to false ceiling level only.				

Sr.No	Description	Qty	Unit	Rate	Amount
3	<p>Providing & fixing full height solid wooden partition finished with laminate on both sides:-</p> <p>(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm bothways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.</p> <p>(ii) Plywood skin:- Providing & fixing 9mm thick MR plywood IS 303 on both sides of the framework.</p> <p>(iii) Finishing:- with 1.00mm thick laminate of approved quality and shade to be finished as per design & pattern shown in Architectural drawing or as directed by the Engineer on both sides</p>	15.00			
	<p>The rate shall include all necessary hardware, making necessary cutouts for electrical conduits / cables & swithboards, AC ducts etc., including necessary support for doors as per drawings/ directed by Engineer..</p> <p>Approved make:-</p> <p>(a) Aluminum extruded sections: Jindal, Hindalco or approved equivalent</p> <p>(b) Plywood:- Greenply, Century, Duro or approved equivalent.</p> <p>(c) Laminte:- Greenlam or equivalent</p> <p>(d) Paint:- Asian, Berger, Jotun or equivalent.</p> <p>Mode of measurement:- Though aluminium frame shall extend up to RCC slab bottom level above false ceiling, partition area below false ceiling shall be measured.</p>				

Sr.No	Description	Qty	Unit	Rate	Amount
4	Fully glazed Door	9.00	Sq M		
	Providing and fixing frameless fully glazed 12mm thk toughened float glass fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items.(DORMA MAKE Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length) Measurement will be taken only upto solid partition level above.				
5	Fully Glazed - Fixed Glass Partition - Patch Fitting	12.00	Sq M		
	Providing and fixing of fixed glass partitions with 12mm thick toughened glass using PT Standard fittings like PT 90/PT 92 of Dorma make at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceilings etc and making the same good with necessary screws, 3M Vinyl sticker as per approved, colour, design and pattern, sealants etc.complete.				
6	Partly Glazed And Partly Paneled Doors.	6.30	Sq M		
	II class T.W. frame of size 75 X 50 mm as per the shape and size given in the drawing. 35 mm thick (finished) flush shutter finished with 1mm laminate on both sides with necessary grooves.8mm thick clear float glass of size 250 X 1400 mm fixed with necessary steam beach beading and etching. DORMA Make or equivalent make hardware fittings like locking arrangements,20 mm dia and 300 mm high SS brush steel finish handles, door closer, hinges, tower bolts,etc,. Fixed to the shutters.				

Sr.No	Description	Qty	Unit	Rate	Amount
7	FALSE CEILING:				
	NOTE:The false ceiling area will be measured in flat area only.				
7 (a)	Gypsum Board False Ceiling	315.00	Sq M		
	Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising				
	Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls around perimeter side of the ceiling. The intermediate channels suspended from ceiling,through starp hangers 25 X 0.5 mm (MF 8)at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A)for light fittings, Air conditioners Ducts,vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.				

Sr.No	Description	Qty	Unit	Rate	Amount
8	TABLE				
8(a)	BRANCH MANAGER'S TABLE:- Size: 2000 mm X 830 mm X 750 mm	1.00	Nos		
	<p>Supplying and installation of Table as per the following description :</p> <p>Table Top: Providing and fixing 18 mm thick IS 303 MR grade plywood with 4mm thick Teak veneer with high gloss PU Coating with necessary intermediate support. Table top shall be supported by 18 mm thick MR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass fixed at a vertical gap of 50mm using SS stud fasteners. The top level of the glass shall be 750mm.</p> <p>Apron (Modesty Panel) made from 18mm thick MR grade plywood finished with teak veneer with melamine Finish & 12 mm thick toughened glass fixed on SS studs & groove pattern as per drawing.</p> <p>Table sides, back & intermediate panels (at 50cm from each sides) made from 18 mm thick MR ply wood finished with 4 thick teak veneer with melamine finish for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.</p>				
	<p>Drawer / Storage cabinet: Box of 450 X 800 X 720 mm shall be provided using 18 mm thick MR grade ply wood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick ply wood & bottom of drawers shall be of 8 mm thick MR grade ply wood. The drawer unit box and individual drawers to be fixed with 4mm veneer finished with melamine polish on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer.</p>				

Sr.No	Description	Qty	Unit	Rate	Amount
	Computer Key board (550 x 375 mm) of metal / PVC of approved make shall be provided. Exposed surfaces of the drawer unit shall have Teak veneer with PU polish. Foot rest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and metallic cable Manager shall be provided in table top.				
	All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade				
	As per drawing and instruction of Architect/Bank, work to be Completed				
8(b)	OFFICER'S TABLE:- Size: 1600 mm X 730 mm X 750 mm	21.00	Nos.		
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick IS 303 MR grade plywood with 1mm thick with necessary intermediate support. Table top shall be supported by 18 mm thick MR grade ply wood with wooden framing. The top of the table shall be provided with equal sized 12mm thick toughened glass fixed. Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1mm laminate & groove pattern as per drawing. Table sides & intermediate panels (at 50cm from each sides) made from 18 mm thick ply wood finished with 1mm thick laminate for all surfaces shall be provided as per drawing.				
	Drawer / Storage cabinet of 400 X 630 X 720 mm shall be provided using 18 mm thick MR grade ply wood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick ply wood & bottom of drawers shall be of 8 mm thick MR grade ply wood. The drawer unit box and individual drawers to be fixed with 1mm laminate on exposed sides and all the internal surfaces shall be 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer.				

Sr.No	Description	Qty	Unit	Rate	Amount
	Computer Key board (550 x 375 mm) of metal / PVC of approved make shall be provided. Foot rest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balacing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and metallic cable Manager shall be provided in table top.				
	All edges to be provided & fixed with teak wood lipping patti finished with melamine polish				
	As per drawing and instruction of Architect/Bank, work to be Completed				
9	Side Tables				
	The side table top top shall be made from 18 mm thick IS 303 MR grade plywood with 1mm thick and all other exposed faces are made of 18 mm marine plywood finished with 1mm thick laminate , and inside painted with 2 coats of enamel over a coat of putty and multiwood/teakwood beading on all exposed edges. Godrej metal body locks, all fixtures, nylon brushes etc complete,				
i	Side table of size 120x45x75cm	18.00	Nos		
ii	Side table 100x45x75	3.00	Nos		
10	Low Level Storage :	55.00	Sq M		
	Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.				

Sr.No	Description	Qty	Unit	Rate	Amount
	Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.				
	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.				
11	Column Paneling	55.00	Sq M		
	Providing and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary aluminium sectional stiffners (as in partition) on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade.				
12	Wall paneling	10.00	Sq M		
	Providing and fixing wall paneling to detail as shown in the drawing with 18mm thick Plywood finished with 1mm thick laminate				
13	Supplying and fixing Roller Blinds of approved make with selected fabric of approved design and shade having powder quotted rod and adjustable string, etc. complete . (Basic Price of Rs 80 Per Sq.Mtr excluding GST) Roller Blind- Vista wall fashion / Mac or equivalent	140.00	Sq M		
14	Painting - Painting the internal walls with 2 coats of plastic emulsion paint over putty finish and a coat of primer in the banking hall	200.00	Sq M		

Sr.No	Description	Qty	Unit	Rate	Amount
15	MEETING ROOM TABLE LAMINATE FINISH				
	Providing & Fixing rectangular Conference Table made of size 1200mm width X 650mm height, T. W. Wood frame work 450mm center to center bothways for table top covered with 12mm thick BWR ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with appd color 1 mm thk. laminate. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound, cleaning the site etc. complete as per the detail drawing and instruction of Engineer.	5.5	RM		
	TOTAL (Excluding GST)				

* GST as applicable to be paid extra