

WIRING DETAIL S:-							
Sl. NO.	RATING	ISOLATOR	FUSE	TYPE OF STARTER	CABLE SIZE IN P.V.CAL (SUPPLY SIDE)	CABLE SIZE IN P.V.CAL (MOTOR SIDE)	EARTHING IN 'CU'
1	UP TO 5.5HP	32A	16A	DOL	40x4 Sq.mm	30x4 Sq.mm	NO 'IF'
2	5.5HP TO 7.5HP	32A	25A	DOL	40x4 Sq.mm	30x4 Sq.mm	NO 'IF'
3	7.5HP TO 10.5HP	63A	25A	S/D	4x105sq.mm	25x40x45sq.mm	NO 'IF'
4	10.5HP TO 15.5HP	63A	32A	S/D	4x165sq.mm	25x40x45sq.mm	NO 'IF'
5	15.5HP TO 20.5HP	63A	50A	S/D	4x205sq.mm	25x40x65sq.mm	NO 'IF'
6	20.5HP TO 25.5HP	125A	50A	S/D	4x255sq.mm	25x40x110 sq.mm	NO 'IF'
7	25.5HP TO 30.5HP	125A	63A	S/D	3.5x205sq.mm	25x40x115 sq.mm	NO 'IF'
8	30.5HP TO 40.5HP	125A	100A	S/D	3.5x305sq.mm	25x40x125 sq.mm	NO 'IF'
9	40.5HP TO 50.5HP	200A	100A	S/D	3.5x405sq.mm	25x40x225 sq.mm	NO 'IF'



A	B	C	D	E	F	G	H	I	J	K	L
---	---	---	---	---	---	---	---	---	---	---	---